# <u>GIBBO</u>



A fresh touch in the Delta Light range is the use of handblown glass globes, a decorative eye-catcher that combines warm tints and materials with the latest LED technology. The Gibbo is a suspended fixture with a base positioned at an angle so that the globe appears to be rolling away. The glass is handblown and is available in transparent, opal or amber tinted versions. The golden brown colour gives the Gibbo a warm presence, which is attractive in composistions above tables and in interiors with warm accents and materials. The base for the Gibbo is available in black or white.

Specification	
Installation Method:	1/2" EMT or 4" J-Box
Adjustability:	Fixed
Rating:	IP20

Performance					
LED Maintenance:	L70>50,000h				
McAdam Step:	2				
CRI:	90				
*SP:	7W				
Delivered Lumens	2700K	3000K			
Gibbo:	738Lm	771Lm			

Listing

ETL certified to US and Canadian safety standards. Warranty

5-year limited warranty.

### Ordering ALL BOXES MUST BE FILLED IN TO CORRECTLY ORDER

Example: GBO-SP27F-B-A-PCPRB-INCD8-120

Luminaire	Power	сст	Function	Finish	Glass Bowl	Style	Installation	Application	Controls***
GBO GIBBO	SP* Standard Power	27 2700K 30 3000K	<b>F</b> Fixed	B Black W White	A Amber C Clear	PC Pendant, 5' cable suspended	MK Mud kit for ½" or %" drywall PRB Surface canopy with black coverplate for 4" junction box	INC Integral Power Supply	<b>D8-120</b> FE ELV dim 120V
					<b>O</b> Opal White		<b>PRW</b> Surface canopy with white coverplate for 4" junction box		
							NA No optional accessory		

\*\*\* Contact factory for additional dimming options

## **Related Products**

Soiree, Miles, Spy C, Hedra C






## **Finish Options**

## GIBBO



#### GLASS BOWL










## **Installation Options**

#### MK - MOUNTING KIT 1






**RB/PRW - COVERPLATE R 114** 

Requires 4" Junction Box

BLACK or WHITE Requires 4" Junction Box

## **Photometric Data**



# **Driver Options**

#### D8

Dimming Control
Phase Control

no

- Dimming Range 10-100%
- Dim to off
- Power Factor @ Full Load >0.9
- Efficiency @ Full Load ≥78
- THD @ Full Load <12%

#### **Dimmer Compatibility**

- Leviton IPE04-1LZ
- Lutron DVELV-300P

As technology changes, please use information above as guidance. For most recent updated information please contact factory. Specifications subject to change without notice.

