



SOLI - 52 93020 Q-DIM

REFERENCE



27118 932Q B

AVAILABLE IN

BLACK 27118 932Q B

GOLD COLOURED 27118 932Q GC

WHITE 27118 932Q W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.4
ADJUSTABILITY	0° to 90° swiveling, 360° rotatable
INFORMATION	REFLECTOR FL-20° EXCL.LED POWER SUPPLY 48V-DC Optional REFLECTORS 30° & 45° available

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	Qbus dim
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, LCA

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 10,3W / CRI>90 (R9: 52) / 3000K / 1281lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	1281lm // 10,3W // 125lm/W
LED TECHNICS (LUMINAIRE)	803lm // 11,8W // 68lm/W

Requirements

SPY 52 TUBE

LED POWER SUPPLY 48V-DC

Accessories

HONEYCOMB 42

SPREAD LENS 42







LINEAR SPREAD LENS 42

SOFTENING LENS 42

GLASS SBL 42

For detailed installation instructions, please consult the manual : [27118_XXXQ_HAND.pdf](#)


FINISH YOUR SPECIFICATION

LED power supplies		# of Fixtures
 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
 300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN Dimtype: non-dimmable	9	
 300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN Dimtype: non-dimmable	23	
 21012 0230 LED POWER SUPPLY 48V-DC / 100W Dimtype: non-dimmable Cutout dimension (mm): 40	9	
 21012 0240 LED POWER SUPPLY 48V-DC / 200W Dimtype: non-dimmable Cutout dimension (mm): 40	19	
Light altering devices		
 19810 0010 B HONEYCOMB 42 SINGLE USE B		
 19810 0020 LINEAR SPREAD LENS 42		

DELTALIGHT

SOLI - 52 93020 Q-DIM


27118 932Q B




19810 0030 SPREAD LENS 42

☐

19810 0040 SOFTENING LENS 42

☐


19810 0050 GLASS SBL 42

☐

19810 0060 B HONEYCOMB 42 DOUBLE USE B

☐

Finish your product



19810 0100 B SPY 52 TUBE B

☐

19810 0100 FBR SPY 52 TUBE FBR

☐

19810 0100 FG SPY 52 TUBE FG

☐


19810 0100 GC SPY 52 TUBE GC

☐

19810 0100 W SPY 52 TUBE W

☐

Replaceable reflector / lens



19810 0180 SPY 52 REFLECTOR 20°

☐

DELTALIGHT

SOLI - 52 93020 Q-DIM

27118 932Q B



19810 0190 SPY 52 REFLECTOR 45°




19810 0240 SPY 52 REFLECTOR 30°




COMPATIBLE COMPOSABLES

SOLISCAPE profile

Available Colours



27111 0020 SOLI - PROFILE 2m



27111 0030 SOLI - PROFILE 3m



Notes: