DELTALIGHT

M - GIBBO 930 DIM5

REFERENCE 23354 9305 W

AVAILABLE IN
BLACK 23354 9305 B
WHITE 23354 9305 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	non adjustable
INFORMATION	EXCL.GLASS EXCL.LED POWER SUPPLY 48V-DC INCL.1 x CABLE SUSPENSION SINGLE AUTOMATIC 1.6m INCL.1 x CABLE 2 x 0.75mm²

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	787lm // 5,8W // 135lm/W
LED TECHNICS (LUMINAIRE)	771lm // 6,7W // 116lm/W

Requirements

BOWL GLASS CLEAR
BOWL GLASS AMBER
BOWL GLASS OPAL WHITE
LED POWER SUPPLY 48V-DC

For detailed installation instructions, please consult the manual : **23354_XXXX_HAND.pdf**

DELTALIGHT

M - GIBBO 930 DIM5

23354 9305 W

FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures

Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



300 89 48 90 LED POWER SUPPLY 48V-DC / 90W — 10

Dimtype: non-dimmable

Cutout dimension (mm): 75



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN — 12

Dimtype: non-dimmable



300 89 48 150 LED POWER SUPPLY 48V-DC / 150W — 17

Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN — 29

Dimtype: non-dimmable



21012 0230 LED POWER SUPPLY 48V-DC / 100W — 12

Dimtype: non-dimmable

Cutout dimension (mm): 40



21012 0240 LED POWER SUPPLY 48V-DC / 200W — 24

Dimtype: non-dimmable

Cutout dimension (mm): 40

To be used with ...



286 67 01 BOWL GLASS CLEAR

DELTALIGHT

M - GIBBO 930 DIM5

23354 9305 W



286 67 02 BOWL GLASS AMBER



286 67 03 BOWL GLASS OPAL WHITE

COMPATIBLE COMPOSABLES

SHIFTLINE M26 profile

Available Colours



420 26 10 00 SLM26 - PROFILE 1m



420 26 20 00 SLM26 - PROFILE 2m



420 26 30 00 SLM26 - PROFILE 3m

SHIFTLINE M26H + SBL

Available Colours

30411 9205 SHIFTLINE M26H + SBL 2m DIM5

30411 9305 SHIFTLINE M26H + SBL 2m DIM5



30412 9205 SHIFTLINE M26H + SBL 3m DIM5

DELTALIGHT

M - GIBBO 930 DIM5

23354 9305 W



30412 9305 SHIFTLINE M26H + SBL 3m DIM5



30413 9205 SHIFTLINE M26H + SBL 4m DIM5



30413 9305 SHIFTLINE M26H + SBL 4m DIM5

SHIFTLINE M26H profile

Available Colours



23359 0000 SLM26H - PROFILE



23359 0010 SLM26H - PROFILE 1m



23359 0020 SLM26H - PROFILE 2m



23359 0030 SLM26H - PROFILE 3m

SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)

Available Colours



23358 0000 SLM26L - PROFILE



23358 0010 SLM26L - PROFILE 1m

M - GIBBO 930 DIM5

23354 9305 W



23358 0020 SLM26L - PROFILE 2m



23358 0030 SLM26L - PROFILE 3m

SHIFTLINE M35R profile

Available Colours



23375 0000 SLM35R - PROFILE



23375 0010 SLM35R - PROFILE 1m



23375 0020 SLM35R - PROFILE 2m



23375 0030 SLM35R - PROFILE 3m

SHIFTLINE M44 profile

Available Colours



23374 0000 SLM44 - PROFILE



23374 0020 SLM44 - PROFILE 2m



23374 0030 SLM44 - PROFILE 3m

DELTALIGHT

M - GIBBO 930 DIM5

23354 9305 W

SPLITLINE M20 ST profile

Available Colours

23397 0000 SPM20 ST - PROFILE

23397 0020 SPM20 ST - PROFILE 2m

23397 0030 SPM20 ST - PROFILE 3m

SPLITLINE M20 profile

Available Colours



420 20 10 00 SPM20 - PROFILE 1m



420 20 20 00 SPM20 - PROFILE 2m



420 20 30 00 SPM20 - PROFILE 3m



23301 0000 SPM20 - PROFILE B

SPLITLINE M52 profile

Available Colours



420 52 10 00 SPM52 - PROFILE 1m



420 52 20 00 SPM52 - PROFILE 2m

DELTALIGHT

M - GIBBO 930 DIM5

23354 9305 W



420 52 30 00 SPM52 - PROFILE 3m



24413 0000 SPM52 - PROFILE

Notes: