
DELTALIGHT




SUPERLOOP SLIM OUT 170 SBL 930

REFERENCE 20579 9300 W

AVAILABLE IN
BLACK 20579 9300 B
FLEMISH BRONZE 20579 9300 FBR
FLEMISH GOLD 20579 9300 FG
GOLD COLOURED 20579 9300 GC
WHITE 20579 9300 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	3.5
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL EXCL.LED POWER SUPPLY 1200-1700mA-DC INCL.3 x CABLE SUSPENSION SINGLE AUTO. 3.0m INCL.1 x CABLE 2 x 0.75mm²

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 51,7-71,4W / CRI>90 (R9: 59) / 3000K / 7128-9460lm
SDCM	SDCM3
LM80	L70 > 30000
LED TECHNICS (LIGHT SOURCE)	9460lm // 71,4W // 132lm/W
LED TECHNICS (LUMINAIRE)	4188lm // 82,1W // 51lm/W

Requirements

LED POWER SUPPLY 1200 / 1700mA-DC DIM
SUPERLOOP POWERBOX H 1200mA
SUPERLOOP POWERBOX H 1700mA

Options

CABLE BASE R / S
COVERSET R 62-90-100 / S 62-80-90
CONNECTION ST / CONNECTION TRIMLESS
SUSPENSION ST / SUSPENSION TRIMLESS

DELTALIGHT


SUPERLOOP SLIM OUT 170 SBL 930

20579 9300 W

For detailed installation instructions, please consult the manual : **20579_XXX0_HAND.pdf**

FINISH YOUR SPECIFICATION

Current supply



203 99 55 ANO CABLE BASE R ANO ☐

203 99 55 B CABLE BASE R B ☐

203 99 55 W CABLE BASE R W ☐



203 99 56 ANO CABLE BASE S ANO ☐

203 99 56 B CABLE BASE S B ☐


203 99 56 W CABLE BASE S W ☐

Power box

of Fixtures

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



321 55 312 ED1 B SUPERLOOP POWERBOX H8 1200mA DIM1 B 1 ☐

Dimtype: 1-10V

321 55 312 ED1 W SUPERLOOP POWERBOX H8 1200mA DIM1 W 1 ☐




321 55 317 ED1 B SUPERLOOP POWERBOX H8 1700mA DIM1 B 1 ☐

Dimtype: 1-10V

SUPERLOOP SLIM OUT 170 SBL 930

20579 9300 W





	321 55 317 ED1 W	SUPERLOOP POWERBOX H8 1700mA DIM1 W	1
	**20548 0025 B**	SUPERLOOP POWERBOX H9 1200mA DIM5 B **Dimtype: DALI**	1
	20548 0025 W	SUPERLOOP POWERBOX H9 1200mA DIM5 W	1

LED power supplies


of Fixtures

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current






	**300 90 130**	LED POWER SUPPLY 1200mA-DC / 60W DIM5 **Dimtype: DALI** **Cutout dimension (mm): 95**	1
	**300 90 132**	LED POWER SUPPLY 1200mA-DC / 70W DIM1 **Dimtype: 1-10V** **Cutout dimension (mm): 80**	1
	**300 90 133**	LED POWER SUPPLY 1700mA-DC / 99W DIM1 **Dimtype: 1-10V** **Cutout dimension (mm): 80**	1
	**21012 0475**	LED POWER SUPPLY 1700mA-DC / 92W DIM5 **Dimtype: DALI**	1

Coversets

	**204 00 62 ANO**	COVERSET R 62 ANO	
	204 00 62 B	COVERSET R 62 B	

SUPERLOOP SLIM OUT 170 SBL 930

20579 9300 W


	204 00 62 W	COVERSET R 62 W
	**204 00 90 ANO**	COVERSET R 90 ANO
	204 00 90 B	COVERSET R 90 B
	204 00 90 W	COVERSET R 90 W
	**204 00 100 ANO**	COVERSET R 100 ANO
	204 00 100 B	COVERSET R 100 B
	204 00 100 W	COVERSET R 100 W
	**204 62 62 ANO**	COVERSET S 62 ANO
	204 62 62 B	COVERSET S 62 B
	204 62 62 W	COVERSET S 62 W
	**204 80 80 ANO**	COVERSET S 80 ANO
	204 80 80 B	COVERSET S 80 B
	204 80 80 W	COVERSET S 80 W
	**204 90 90 ANO**	COVERSET S 90 ANO
	204 90 90 B	COVERSET S 90 B

SUPERLOOP SLIM OUT 170 SBL 930

20579 9300 W


204 90 90 W COVERSET S 90 W

Suspension parts



328 10 01 SUSPENSION TRIMLESS O.F.A.

Cutout dimension (mm): 62 (CONCRETE: 102)




15225 0340 B SUSPENSION ST B

Cutout dimension (mm): 27

15225 0340 W SUSPENSION ST W

Electric connection parts



328 10 03 CONNECTION TRIMLESS O.F.A.

Cutout dimension (mm): 62 (CONCRETE: 102)



15225 0360 B CONNECTION ST B

Cutout dimension (mm): 43

15225 0360 W CONNECTION ST W

Notes: