





M26L - HALOSCAN HP 92721 DIM5

23130 9225 W

AVAILABLE IN
NOIR 23130 9225 B
BLANC 23130 9225 W



[View on website](#)



General info	
LOCATION	interieur
INSTALLATION	Systèmes basse tension Monté sur systèmes basse tension
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° à 45° inclinable, 355° rotatif
INFORMATION	LENS FL-21° EXCL.LED POWER SUPPLY 48V-DC
Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	D
CERTIFICATION	CB, ENEC
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 11,6W / CRI>90 (R9: 60) / 2700K / 1458lm
RVALUES	rf: 89 / Rg: 100
SDMC	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	21°
LED TECHNICS (LIGHT SOURCE)	1458lm // 11,6W // 125lm/W
LED TECHNICS (LUMINAIRE)	1195lm // 13,3W // 90lm/W

Remarks

Take a look at our [MAGNETIC PROFILES](#) movie

Requirements

LED POWER SUPPLY 48V-DC

Accessories







HALOSCAN HONEYCOMB
 HALOSCAN LINEAR SPREAD LENS

M26L - HALOSCAN HP 92721 DIM5

23130 9225 W

For detailed installation instructions, please consult the manual : [23130_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION









les alimentations led		# of Fixtures
web2print_power_supply_info_box		Min current Max current
	300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN Dimtype: non dimmable	7 ☐
	300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN Dimtype: non dimmable	17 ☐
	21012 0230 LED POWER SUPPLY 48V-DC / 100W Dimtype: non dimmable Cutout dimension (mm): 40	7 ☐
	21012 0240 LED POWER SUPPLY 48V-DC / 200W Dimtype: non dimmable Cutout dimension (mm): 40	14 ☐
modifier les dispositifs de lumière		
	23110 0040 HALOSCAN LINEAR SPREAD LENS	☐
	23110 0050 B HALOSCAN HONEYCOMB B	☐

DELTALIGHT

M26L - HALOSCAN HP 92721 DIM5

23130 9225 W

COMPATIBLE COMPOSABLES

SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)		Available Colours
	23358 0000 SLM26L - PROFILE	 
	23358 0010 SLM26L - PROFILE 1m	 
	23358 0020 SLM26L - PROFILE 2m	         
	23358 0030 SLM26L - PROFILE 3m	         
SHIFTLINE M35R profile		Available Colours
	23375 0000 SLM35R - PROFILE	
	23375 0010 SLM35R - PROFILE 1m	
	23375 0020 SLM35R - PROFILE 2m	
	23375 0030 SLM35R - PROFILE 3m	

Notes:

DELTALIGHT

M26L - HALOSCAN HP 92721 DIM5

23130 9225 W