



## OML50 - PRISMATIC LENS DU HO 1312mm 940 DIM5

31634 9405 B

AVAILABLE IN  
**BLACK** 31634 9405 B

 [View on website](#)



General info	
<b>LOCATION</b>	indoor
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	1.8
<b>INFORMATION</b>	INCL.DIMMABLE LED POWER SUPPLY (DALI-2 standard) CABLING 1 CIRCUIT
Electrical info	
<b>ELECTRICAL</b>	220-240V / 0 50-60Hz
<b>CLASS</b>	I
<b>POWER SUPPLY</b>	YES
<b>DIM TYPE</b>	DALI
<b>ENERGY CLASS</b>	D
<b>CERTIFICATES</b>	EPD, RCM
Lightsource info	
<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	DOWN: LED cluster 31W / CRI>90 (R9: 50) / 4000K / 4850lm UP: LED cluster 24,2W / CRI>90 (R9: 50) / 4000K / 3642lm
<b>TM-30 VALUES</b>	Rf: 90 / Rg: 101
<b>SDCM</b>	SDCM3
<b>RISKGROUP</b>	RG1
<b>LM80</b>	L80 > 60000
<b>LED TECHNICS (LIGHT SOURCE)</b>	DOWN: 4850lm // 31W // 160lm/W UP: 3642lm // 24,2W // 151lm/W

### Options

WIRELESS CONTROL DIM5

Notes: