



HALOSCAN ON 2 MP 92721 DIM8



23149 9228 W-W

AVAILABLE IN

BLACK-BLACK 23149 9228 B-B

BLACK-GOLD COLORED 23149 9228 B-GC

WHITE-WHITE 23149 9228 W-W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.7
ADJUSTABILITY	0° to 45° swiveling, 355° rotatable
INFORMATION	LENS FL-21° INCL.DIMMABLE LED POWER SUPPLY 350mA-DC

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED array 5,8W / CRI>90 (R9: 60) / 2700K / 753lm)
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	21°
LED TECHNICS (LIGHT SOURCE)	1506lm // 11,6W // 129lm/W
LED TECHNICS (LUMINAIRE)	1175lm // 13,3W // 88lm/W


Accessories

HALOSCAN HONEYCOMB
HALOSCAN LINEAR SPREAD LENS
HALOSCAN KAP MP

For detailed installation instructions, please consult the manual : [23149_XXX8_HAND.pdf](#)


FINISH YOUR SPECIFICATION

Light altering devices




23110 0040

HALOSCAN LINEAR SPREAD LENS

☐

23110 0050 B

HALOSCAN HONEYCOMB B

☐

23110 0060 B

HALOSCAN KAP MP B

☐

23110 0060 W

HALOSCAN KAP MP W

☐

Notes: