
DELTALIGHT




SOLI - LINE 90 DOWN 930 Q-DIM

REFERENCE 27156 930Q B

AVAILABLE IN
BLACK 27156 930Q B
WHITE 27156 930Q W





View on website

General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	non adjustable
INFORMATION	EXCL.LED POWER SUPPLY 48V-DC

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	Qbus dim
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED flex 18W / CRI>90 (R9: 60) / 3000K / 2240lm
SDCM	SDCM3
LM80	L70 > 30000
LED TECHNICS (LIGHT SOURCE)	2240lm // 18W // 124lm/W
LED TECHNICS (LUMINAIRE)	1485lm // 20,7W // 72lm/W

Requirements

LED POWER SUPPLY 48V-DC

For detailed installation instructions, please consult the manual : **27156_XXXQ_HAND.pdf**

DELTALIGHT

SOLI - LINE 90 DOWN 930 Q-DIM

27156 930Q B


FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures


of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN — 4

Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN — 11


Dimtype: non-dimmable



21012 0230 LED POWER SUPPLY 48V-DC / 100W — 4

Dimtype: non-dimmable

Cutout dimension (mm): 40



21012 0240 LED POWER SUPPLY 48V-DC / 200W — 9


Dimtype: non-dimmable

Cutout dimension (mm): 40


COMPATIBLE COMPOSABLES

SOLISCAPE profile

Available Colours



27111 0020 SOLI - PROFILE 2m



27111 0030 SOLI - PROFILE 3m

Notes:

SOLI - LINE 90 DOWN 930 Q-DIM

27156 930Q B