



BOXY XL R C 92737



251 73 21 923 B-B

AVAILABLE IN

BLACK-BLACK 251 73 21 923 B-B

WHITE-BLACK 251 73 21 923 W-B

WHITE-WHITE 251 73 21 923 W-W



[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.8
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR FL-37° INCL.DIMMABLE LED POWER SUPPLY 500mA-DC INCL.1 x CABLE SUSPENSION SINGLE AUTO. 1.6m INCL.1 x CABLE 2 x 0,75mm ²
Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, RCM
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 16,3W / CRI>90 (R9: 60) / 2700K / 2209lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	37°
LED TECHNICS (LIGHT SOURCE)	2209lm // 16,3W // 136lm/W
LED TECHNICS (LUMINAIRE)	1969lm // 18,7W // 105lm/W

Options

COVERSET R 90-100

SUSPENSION + CONNECTION TRIMLESS

Accessories

HONEYCOMB 78


SOFTENING LENS 78

GLASS SBL 78

For detailed installation instructions, please consult the manual : [251_73_21_XXX_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Miscellaneous control equipment




300 90 004 ED8 WIRELESS CONTROL DIM8

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 40

☐

Coversets




204 00 90 ANO COVERSET R 90 ANO

☐

204 00 90 B COVERSET R 90 B

☐

204 00 90 W COVERSET R 90 W

☐


204 00 100 ANO COVERSET R 100 ANO

☐


204 00 100 B COVERSET R 100 B

☐

204 00 100 W COVERSET R 100 W

☐

Suspension parts



328 10 02 SUSPENSION + CONNECTION TRIMLESS O.F.A.

Cutout dimension (mm): 62 (CONCRETE: 102)


☐

DELTALIGHT

BOXY XL R C 92737

251 73 21 923 B-B

Light altering devices



201 02 01 B HONEYCOMB 78 B

Ø78

☐

201 02 04 SOFTENING LENS 78

Ø78

☐

201 02 05 GLASS SBL 78

Ø78

☐

Notes: