





Image may differ from the actual product
Consult drawing for correct size and structure

INFORM 40 SQ 180 DOWN 93063 DIM5

30713 9335 B-B

DISPONIBLE EN
NOIR-NOIR 30713 9335 B-B
BLANC-NOIR 30713 9335 W-B



[Voir sur le site Web](#)




Informations générales	
EMPLACEMENT	interieur
INSTALLATION	Plafond Applique,Plafond Suspendu
INDICE DE PROTECTION	IP20
POIDS (KG)	2.9
ORIENTATION	non réglable
INFORMATIONS	INCL.DIMMABLE LED POWER SUPPLY (DALI DT6) Power selection to be set on driver EXCL.CABLE SUSPENSION
Informations électriques	
ÉLECTRIQUE	220-240V / 0 50-60Hz
CLASSE	I
ALIMENTATION	YES
TYPE DIM	DALI
CLASSE D'ÉNERGIE	E
Info Source lumineuse	
LIGHTSOURCE NAME	LED
SOURCE DE LUMIÈRE	HO: LED cluster 27W / CRI>90 (R9: 50) / 3000K / 3821lm Or LED cluster 16,3W / CRI>90 (R9: 50) / 3000K / 2534lm
VALEURS TM-30	Rf: 92 / Rg: 100 rf: 92 / Rg: 100
SDCM	SDCM3
GROUPE DE RISQUE	RG1
LM80	L80 > 60000
BEAMANGLE	63°
TECHNIQUES LED (SOURCE LUMINEUSE)	HO: 3821lm // 27W // 141lm/W Or 2534lm // 16,3W // 155lm/W
TECHNIQUES LED (LUMINAIRE)	HO: 2644lm // 31W // 85lm/W Or 1753lm // 18,7W // 94lm/W
Références optionnelles	
INF40 SQ 160/180 - SUSPENSION SET	
CABLE BASE R / S	

Pour des instructions d'installation détaillées, veuillez consulter le manuel : [30713_XXX5_HAND.pdf](#)

TERMINEZ VOTRE SPÉCIFICATION

le cable d'alimentation



203 99 55 ANO CABLE BASE R ANO

☐

203 99 55 B CABLE BASE R B

☐

203 99 55 W CABLE BASE R W

☐


203 99 56 ANO CABLE BASE S ANO

☐

203 99 56 B CABLE BASE S B

☐

203 99 56 W CABLE BASE S W

☐

les accessoires de fixations



30710 0010 B INF40 SQ 160/180 - SUSPENSION SET 1,6m B

☐

30710 0010 W INF40 SQ 160/180 - SUSPENSION SET 1,6m W

☐


30710 0030 B INF40 SQ 160/180 - SUSPENSION SET 3,0m B

☐

30710 0030 W INF40 SQ 160/180 - SUSPENSION SET 3,0m W

☐

DELTALIGHT

INFORM 40 SQ 180 DOWN 93063 DIM5

30713 9335 B-B

Notes: