



M20/M26H - SPY FOCUS MP 930 DIM5

23373 9305 FG



AVAILABLE IN

BLACK 23373 9305 B

FLEMISH BRONZE 23373 9305 FBR

FLEMISH GOLD 23373 9305 FG

WHITE 23373 9305 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	0° to 90° swiveling, 355° rotatable
INFORMATION	ADJUSTABLE BEAM 12°-45° INCL.CLIP 48V ADAPTER EXCL.LED POWER SUPPLY 48V-DC

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	CB, EAC, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 17,2W / CRI>90 (R9: 52) / 3000K / 210lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	12°-45°
LED TECHNICS (LIGHT SOURCE)	210lm // 17,2W // 123lm/W
LED TECHNICS (LUMINAIRE)	735lm // 19,8W // 37lm/W

Remarks

[Take a look at our MAGNETIC PROFILES movie](#)

Requirements

LED POWER SUPPLY 48V-DC

For detailed installation instructions, please consult the manual : [23373_9X05_HAND.pdf](#)

FINISH YOUR SPECIFICATION


LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




300 89 48 90 LED POWER SUPPLY 48V-DC / 90W

4

Dimtype: non-dimmable


Cutout dimension (mm): 75



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

4


Dimtype: non-dimmable



300 89 48 150 LED POWER SUPPLY 48V-DC / 150W

6


Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

11

Dimtype: non-dimmable




21012 0230 LED POWER SUPPLY 48V-DC / 100W

5

Dimtype: non-dimmable

Cutout dimension (mm): 40



21012 0240 LED POWER SUPPLY 48V-DC / 200W

10

Dimtype: non-dimmable

Cutout dimension (mm): 40

Power box

of Fixtures





of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current

DELTALIGHT

M20/M26H - SPY FOCUS MP 930 DIM5

23373 9305 FG

	23380 0010 B SLM26H - POWERBOX 48V-DC / 96W B	5	☐
Dimtype: non-dimmable			
23380 0010 W SLM26H - POWERBOX 48V-DC / 96W W		5	☐
	23380 0020 B SLM26H - MID POWERBOX 48V-DC / 96W B	5	☐
Dimtype: non-dimmable			
23380 0020 W SLM26H - MID POWERBOX 48V-DC / 96W W		5	☐





COMPATIBLE COMPOSABLES

SHIFTLINE M26H + SBL		Available Colours
	<u>30411 9205</u> SHIFTLINE M26H + SBL 2m DIM5	
	<u>30411 9305</u> SHIFTLINE M26H + SBL 2m DIM5	
	<u>30412 9205</u> SHIFTLINE M26H + SBL 3m DIM5	
	<u>30412 9305</u> SHIFTLINE M26H + SBL 3m DIM5	
	<u>30413 9205</u> SHIFTLINE M26H + SBL 4m DIM5	
	<u>30413 9305</u> SHIFTLINE M26H + SBL 4m DIM5	



DELTALIGHT

M20/M26H - SPY FOCUS MP 930 DIM5

23373 9305 FG

SHIFTLINE M26H profile		Available Colours
	23359 0000 SLM26H - PROFILE	
	23359 0010 SLM26H - PROFILE 1m	
	23359 0020 SLM26H - PROFILE 2m	
	23359 0030 SLM26H - PROFILE 3m	



SPLITLINE M20 ST profile		Available Colours
	23397 0000 SPM20 ST - PROFILE	
	23397 0020 SPM20 ST - PROFILE 2m	
	23397 0030 SPM20 ST - PROFILE 3m	

SPLITLINE M20 profile		Available Colours
	420 20 10 00 SPM20 - PROFILE 1m	
	420 20 20 00 SPM20 - PROFILE 2m	

DELTALIGHT

M20/M26H - SPY FOCUS MP 930 DIM5

23373 9305 FG

	420 20 30 00 SPM20 - PROFILE 3m	
	23301 0000 SPM20 - PROFILE B	

Notes: