
DELTALIGHT




# M20/M26H - OCTAV 39 92720 DIM5

**REFERENCE** 29022 9225 FBR

AVAILABLE IN
**BLACK** 29022 9225 B
**FLEMISH BRONZE** 29022 9225 FBR
**FLEMISH GOLD** 29022 9225 FG
**GOLD COLOURED** 29022 9225 GC
**WHITE** 29022 9225 W




View on website

| General info | |
|---|---|
| **LOCATION** | indoor |
| **INSTALLATION** | Low voltage systems Low voltage system mounted |
| **INGRESS PROTECTION** | IP20 |
| **WEIGHT (KG)** | 0.4 |
| **ADJUSTABILITY** | 0° to 85° swiveling, 355° rotatable |
| **INFORMATION** | REFLECTOR FL-20°<br>EXCL.LED POWER SUPPLY 48V-DC |

| Electrical info | |
|---|---|
| **ELECTRICAL** | 48V-DC |
| **CLASS** | III |
| **DIM TYPE** | DALI |
| **ENERGY CLASS** | E |
| **CERTIFICATES** | CB, ENEC |

| Lightsource info | |
|---|---|
| **LIGHTSOURCE NAME** | LED |
| **LIGHTSOURCE** | LED array 8,6W / CRI>90 (R9: 60) / 2700K / 1041lm |
| **TM-30 VALUES** | Rf: 89 / Rg: 100 |
| **SDCM** | SDCM1 |
| **RISKGROUP** | RG1 |
| **LM80** | L90B10 > 50000 |
| **BEAMANGLE** | 20° |
| **LED TECHNICS (LIGHT SOURCE)** | 1041lm // 8,6W // 121lm/W |
| **LED TECHNICS (LUMINAIRE)** | 652lm // 9,9W // 66lm/W |

**Remarks**

**Take a look at our MAGNETIC PROFILES movie**

**Requirements**

SPY 39 L TUBE
LED POWER SUPPLY 48V-DC

For detailed installation instructions, please consult the manual : **29022_XXX5_HAND.pdf**

# M20/M26H - OCTAV 39 92720 DIM5

29022 9225 FBR


## FINISH YOUR SPECIFICATION

### LED power supplies

**# of Fixtures**


**Min current | Max current**

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.





**300 89 48 100** LED POWER SUPPLY 48V-DC / 100W DIN — 10

**Dimtype: non-dimmable**




**300 89 48 240** LED POWER SUPPLY 48V-DC / 240W DIN — 24


**Dimtype: non-dimmable**




**21012 0230** LED POWER SUPPLY 48V-DC / 100W — 10

**Dimtype: non-dimmable**

**Cutout dimension (mm): 40**





**21012 0240** LED POWER SUPPLY 48V-DC / 200W — 20

**Dimtype: non-dimmable**

**Cutout dimension (mm): 40**

### Finish your product




**24144 0020 B** SPY 39 L TUBE B

**24144 0020 FBR** SPY 39 L TUBE FBR

**24144 0020 FG** SPY 39 L TUBE FG





**24144 0020 GC** SPY 39 L TUBE GC




**24144 0020 W** SPY 39 L TUBE W

# M20/M26H - OCTAV 39 92720 DIM5

29022 9225 FBR

## COMPATIBLE COMPOSABLES


| SHIFTLINE M26H + SBL | Available Colours |
|---|---|
|  **30411 9205** SHIFTLINE M26H + SBL 2m DIM5 | |
|  **30411 9305** SHIFTLINE M26H + SBL 2m DIM5 | |
|  **30412 9205** SHIFTLINE M26H + SBL 3m DIM5 | |
|  **30412 9305** SHIFTLINE M26H + SBL 3m DIM5 | |
|  **30413 9205** SHIFTLINE M26H + SBL 4m DIM5 | |
|  **30413 9305** SHIFTLINE M26H + SBL 4m DIM5 | |

| SHIFTLINE M26H profile | Available Colours |
|---|---|
|  **23359 0000** SLM26H - PROFILE | |
|  **23359 0010** SLM26H - PROFILE 1m | |
|  **23359 0020** SLM26H - PROFILE 2m | |

DELTALIGHT

# M20/M26H - OCTAV 39 92720 DIM5

29022 9225 FBR




**23359 0030** SLM26H - PROFILE 3m

## SPLITLINE M20 ST profile

Available Colours




**23397 0000** SPM20 ST - PROFILE





**23397 0020** SPM20 ST - PROFILE 2m





**23397 0030** SPM20 ST - PROFILE 3m

## SPLITLINE M20 profile


Available Colours





**420 20 10 00** SPM20 - PROFILE 1m




**420 20 20 00** SPM20 - PROFILE 2m




**420 20 30 00** SPM20 - PROFILE 3m




**23301 0000** SPM20 - PROFILE B

Notes: