

## INFORM SQ P200-4 DOWN 94067

25515 9420 W-W



AVAILABLE IN

**BLACK-BLACK** 25515 9420 B-B

**BLACK-FLEMISH GOLD** 25515 9420 B-FG

**WHITE-BLACK** 25515 9420 W-B

**WHITE-WHITE** 25515 9420 W-W



[View on website](#)



### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Ceiling Suspended
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	1.4
<b>ADJUSTABILITY</b>	non adjustable
<b>INFORMATION</b>	48 x REFLECTOR FL-67° EXCL.LED POWER SUPPLY 400/600mA-DC INCL.2 x CABLE SUSPENSION SINGLE AUTO. 1,6m POWER VIA CABLE SUSPENSION

### Electrical info

<b>CLASS</b>	III
<b>DIM TYPE</b>	depending on power supply
<b>ENERGY CLASS</b>	E
<b>CERTIFICATES</b>	CB, ENEC, EPD

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	2 x (LED cluster 7-11,2W / CRI>90 (R9: 50) / 4000K / 1114-1610lm)
<b>TM-30 VALUES</b>	Rf: 90 / Rg: 101
<b>SDCM</b>	SDCM3
<b>RISKGROUP</b>	RG1
<b>LM80</b>	L80 > 60000
<b>BEAMANGLE</b>	67°
<b>LED TECHNICS (LIGHT SOURCE)</b>	3220lm // 22,4W // 144lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	2811lm // 25,8W // 109lm/W

### Requirements

INFORM SQ POWERBOX 50W (DIM5)

INFORM POWER SUPPLY 25W + SUSPENSION+CONNECTION ST

For detailed installation instructions, please consult the manual : [25515\\_XXX0\\_HAND.pdf](#)

# DELTALIGHT

## INFORM SQ P200-4 DOWN 94067

25515 9420 W-W

### FINISH YOUR SPECIFICATION

#### Power box

#### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



**25510 0010 B** INFORM SQ POWERBOX 50W B

1

Dimtype: non-dimmable

**25510 0010 W** INFORM SQ POWERBOX 50W W

1



**25510 0015 B** INFORM SQ POWERBOX 50W DIM5 B

1

Dimtype: DALI

**25510 0015 W** INFORM SQ POWERBOX 50W DIM5 W

1


#### LED power supplies

#### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



**25510 0395** INFORM POWER SUPPLY 25W DIM5

1

Dimtype: DALI



**25510 0440** INFORM POWER SUPPLY 25W

1

Dimtype: non-dimmable

#### Electric connection parts

#### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current

# DELTALIGHT

## INFORM SQ P200-4 DOWN 94067

25515 9420 W-W



**15225 0350 B** SUSPENSION + CONNECTION ST B

2 needed

**Cutout dimension (mm): 27**

**15225 0350 W** SUSPENSION + CONNECTION ST W

2 needed

Notes: