



SPY 39 L ON 1 93040 DIM8



24138 9338 B-B

AVAILABLE IN

NOIR-NOIR 24138 9338 B-B

ENTIÈREMENT BLANC 24138 9338 FW

BLANC-BLANC 24138 9338 W-W



[View on website](#)



General info	
LOCATION	interieur
INSTALLATION	Plafond Applique
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.6
ADJUSTABILITY	0° à 85° inclinable, 355° rotatif
INFORMATION	REFLECTOR WFL-40° INCL.DIMMABLE LED POWER SUPPLY 350/500mA-DC Current selection via jumper on power supply
Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY INCLUDED	YES
DIM TYPE	fin de phase
ENERGY CLASS	D
CERTIFICATION	CB, ENEC, RCM
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm
RVALUES	rf: 90 / Rg: 99
SDMC	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	40°
LED TECHNICS (LIGHT SOURCE)	1089lm // 8,6W // 127lm/W
LED TECHNICS (LUMINAIRE)	737lm // 9,9W // 75lm/W

Requirements

SPY 39 L TUBE

For detailed installation instructions, please consult the manual : [24138_XXX8_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Terminez votre produit

	<u>24144 0020 B</u>	SPY 39 L TUBE B	☐
	<u>24144 0020 FBR</u>	SPY 39 L TUBE FBR	☐
	<u>24144 0020 FG</u>	SPY 39 L TUBE FG	☐
	<u>24144 0020 GC</u>	SPY 39 L TUBE GC	☐
	<u>24144 0020 W</u>	SPY 39 L TUBE W	☐

Notes: