



ENTERO SQ-M IP TW 94018



28563 9010 B

AVAILABLE IN

BLACK 28563 9010 B

FULL WHITE 28563 9010 FW

GOLD COLOURED 28563 9010 GC



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	square - 92 x 92
RECESSED DEPTH (MM)	145
THICKNESS OF MOUNTING SURFACE (MM)	12,5 or 25
INGRESS PROTECTION	IP44/20
WEIGHT (KG)	0.42
ADJUSTABILITY	0° to 20° swiveling, 355° rotatable
INFORMATION	REFLECTOR SP-18° EXCL.LED POWER SUPPLY 500mA-DC TW - (DALI DT8)

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 9W / CRI>90 (R9: 50) / 1800K-4000K / 979lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	18°
LED TECHNICS (LIGHT SOURCE)	979lm // 9W // 109lm/W
LED TECHNICS (LUMINAIRE)	638lm // 10,4W // 62lm/W

Requirements


LED POWER SUPPLY 500mA-DC TW

For detailed installation instructions, please consult the manual : [28563_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Stucanet	-
 Wood	-
 Stretched ceiling	-

FINISH YOUR SPECIFICATION

LED power supplies	# of Fixtures
 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.	Min current Max current
 21012 0355 LED POWER SUPPLY 500mA-DC 2CH TW DIM5 Dimtype: DALI Cutout dimension (mm): 85	2

Notes: