



Image may differ from the actual product  
Consult drawing for correct size and structure



## INFORM 40 SQ 180 DOWN 93063 DIM5

30713 9335 W-B

AVAILABLE IN

**BLACK-BLACK** 30713 9335 B-B

**WHITE-BLACK** 30713 9335 W-B



[View on website](#)



| General info                |                                                                                                                      |
|-----------------------------|----------------------------------------------------------------------------------------------------------------------|
| LOCATION                    | indoor                                                                                                               |
| INSTALLATION                | Ceiling Surface mounted,Ceiling Suspended                                                                            |
| INGRESS PROTECTION          | IP20                                                                                                                 |
| WEIGHT (KG)                 | 2.9                                                                                                                  |
| ADJUSTABILITY               | non adjustable                                                                                                       |
| INFORMATION                 | INCL.DIMMABLE LED POWER SUPPLY (DALI DT6)<br>Power selection to be set on driver<br>EXCL.CABLE SUSPENSION            |
| Electrical info             |                                                                                                                      |
| ELECTRICAL                  | 220-240V / 0 50-60Hz                                                                                                 |
| CLASS                       | I                                                                                                                    |
| POWER SUPPLY                | YES                                                                                                                  |
| DIM TYPE                    | DALI                                                                                                                 |
| ENERGY CLASS                | E                                                                                                                    |
| Lightsource info            |                                                                                                                      |
| LIGHTSOURCE NAME            | LED                                                                                                                  |
| LIGHTSOURCE                 | HO: LED cluster 27W / CRI>90 (R9: 50) / 3000K / 3821lm<br>Or<br>LED cluster 16,3W / CRI>90 (R9: 50) / 3000K / 2534lm |
| TM-30 VALUES                | Rf: 92 / Rg: 100<br>rf: 92 / Rg: 100                                                                                 |
| SDCM                        | SDCM3                                                                                                                |
| RISKGROUP                   | RG1                                                                                                                  |
| LM80                        | L80 > 60000                                                                                                          |
| BEAMANGLE                   | 63°                                                                                                                  |
| LED TECHNICS (LIGHT SOURCE) | HO: 3821lm // 27W // 141lm/W<br>Or<br>2534lm // 16,3W // 155lm/W                                                     |
| LED TECHNICS (LUMINAIRE)    | HO: 2644lm // 31W // 85lm/W<br>Or<br>1753lm // 18,7W // 94lm/W                                                       |


### Options

INF40 SQ 160/180 - SUSPENSION SET  
CABLE BASE R / S

For detailed installation instructions, please consult the manual : [30713\\_XXX5\\_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Current supply



**203 99 55 ANO**

CABLE BASE R ANO

☐

**203 99 55 B**

CABLE BASE R B

☐

**203 99 55 W**

CABLE BASE R W

☐



**203 99 56 ANO**

CABLE BASE S ANO

☐

**203 99 56 B**

CABLE BASE S B


☐

**203 99 56 W**

CABLE BASE S W

☐

Fixation components



**30710 0010 B**


INF40 SQ 160/180 - SUSPENSION SET 1,6m B

☐

**30710 0010 W**

INF40 SQ 160/180 - SUSPENSION SET 1,6m W

☐



**30710 0030 B**

INF40 SQ 160/180 - SUSPENSION SET 3,0m B

☐

**30710 0030 W**

INF40 SQ 160/180 - SUSPENSION SET 3,0m W

☐

# DELTALIGHT

## INFORM 40 SQ 180 DOWN 93063 DIM5

30713 9335 W-B

Notes: