





SUPERNOVA FLAT 95 PRISMATIC 930 DIM5

20637 9305 B

AVAILABLE IN
BLACK 20637 9305 B
WHITE 20637 9305 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted,Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	15,9
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC PRISMATIC INCL.DIMMABLE LED POWER SUPPLY 1860mA

Electrical info

ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, LCA, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 79,4W / CRI>90 (R9: 68) / 3000K / 11477lm
TM-30 VALUES	Rf: 89 / Rg: 97
SDCM	SDCM3
LM80	L70 > 60000
LED TECHNICS (LIGHT SOURCE)	11477lm // 79,4W // 144lm/W
LED TECHNICS (LUMINAIRE)	8583lm // 91,3W // 94lm/W

Options

SUSPENSION SET 25 DIM 3m
 CABLE BASE R / S
 COVERSET R 62-90-100 / S 62-80-90
 CENTRAL ROD SUSPENSION SUPERNOVA FLAT 1m
 CENTRAL SUSPENSION SUPERNOVA FLAT

For detailed installation instructions, please consult the manual : [20637_XXX5_HAND.pdf](#)

DELTA



LIGHT

SUPERNOVA FLAT 95 PRISMATIC 930 DIM5



20637 9305 B

FINISH YOUR SPECIFICATION

Current supply

	203 99 55 ANO CABLE BASE R ANO	☐
	203 99 55 B CABLE BASE R B	☐
	203 99 55 W CABLE BASE R W	☐
	203 99 56 ANO CABLE BASE S ANO	☐
	203 99 56 B CABLE BASE S B	☐
	203 99 56 W CABLE BASE S W	☐





Coversets

	204 00 62 ANO COVERSET R 62 ANO	☐
	204 00 62 B COVERSET R 62 B	☐
	204 00 62 W COVERSET R 62 W	☐
	204 00 90 ANO COVERSET R 90 ANO	☐
	204 00 90 B COVERSET R 90 B	☐
	204 00 90 W COVERSET R 90 W	☐


DELTALIGHT

SUPERNOVA FLAT 95 PRISMATIC 930 DIM5

20637 9305 B

	<u>204 00 100 ANO</u> COVERSET R 100 ANO	☐
	<u>204 00 100 B</u> COVERSET R 100 B	☐
	<u>204 00 100 W</u> COVERSET R 100 W	☐
	<u>204 62 62 ANO</u> COVERSET S 62 ANO	☐
	<u>204 62 62 B</u> COVERSET S 62 B	☐
	<u>204 62 62 W</u> COVERSET S 62 W	☐
	<u>204 80 80 ANO</u> COVERSET S 80 ANO	☐
	<u>204 80 80 B</u> COVERSET S 80 B	☐
	<u>204 80 80 W</u> COVERSET S 80 W	☐
	<u>204 90 90 ANO</u> COVERSET S 90 ANO	☐
	<u>204 90 90 B</u> COVERSET S 90 B	☐
	<u>204 90 90 W</u> COVERSET S 90 W	☐

Suspension parts


	<u>274 97 10 B</u> CENTRAL ROD SUSPENSION SUPERNOVA FLAT 1m B	☐
---	--	--------------------------

DELTALIGHT


SUPERNOVA FLAT 95 PRISMATIC 930 DIM5

20637 9305 B

274 97 10 W CENTRAL ROD SUSPENSION SUPERNOVA FLAT 1m W

☐

328 25 43 ED SUSPENSION SET 25 DIM 3m

☐

328 26 23 B CENTRAL SUSPENSION SUPERNOVA FLAT 3m B

☐

328 26 23 W CENTRAL SUSPENSION SUPERNOVA FLAT 3m W

☐

Electric connection parts



15225 0360 B CONNECTION ST B

☐

Cutout dimension (mm): 43

15225 0360 W CONNECTION ST W

☐

Notes: