



HELI X



As a small wall recessed luminaire, Heli is perfect as a guidance light. Installed in a corridor or as a safety light for steps, Heli does the trick. Heli X is an exterior-rated square fixture, creating a dramatic wedge of light on the adjacent floor surface.

Specification	
Wall Cut-out:	2 ¹⁵ / ₁₆ " x 3 ⁷ / ₁₆ "
Adjustability:	Fixed
Rating:	IP54

Performance	
LED Maintenance:	L90>150,000h
McAdam Step:	3
CRI:	90
*SP:	1W

Delivered Lumens	
Heli X:	3000K 20Lm

Listing

ETL certified to US and Canadian safety standards.

Warranty

5-year limited warranty.

Ordering

ALL BOXES MUST BE FILLED IN TO CORRECTLY ORDER

Example: HLI-SP30FXO-N-NARMTD1-UNV

Luminaire	Power	CCT	Function	Style	Finish	Installation	Application	Controls***
HLI HELI	SP* Standard Power	30 3000K	FX Fixed, Exterior Use	O Open	A Alu Grey N Anthracite	CB Enclosed box for concrete NA No optional accessory	RMT Remote Power Supply	D1-UNV 0-10V dim 120-277V D8-120 FE ELV dim 120V

*** Contact factory for additional dimming options


Related Products

Heli (interior), Logic W



Finish Options


HELI X



ALU GREY




ANTHRACITE



LIGHT EFFECT

Photometric Data

HELI X




Installation Options

REMOTE DRIVER

(With Controls D8)

A: 8" x B: 2"-1/2 x C: 2"-1/2
A: 203mm x B: 64mm x C: 64mm

- For Remote application
- ETL Listed
- Damp rated




REMOTE DRIVER


(With Controls D1)

A: 8" x B: 2"-3/16 x C: 4"-1/4
A: 203mm x B: 72mm x C: 108mm

- For Remote application
- ETL Listed
- Damp rated



CB - CONCRETE BOX 187





Driver Options

D1

- Dimming Control 0-10V
- Dimming Range 1-100%
- Dim to off yes at 0.7mA
- Power Factor @ Full Load >0.9
- Efficiency @ Full Load ≥87
- THD @ Full Load <20%
- Title 24 Compliant

Dimmer Compatibility

- Leviton IP710-DLZ
- Lutron DDTV-XX
- WattStopper ADF-120277
- Synergy Lighting Controls ISD BC

D8

- Dimming Control Phase Control
- Dimming Range 10-100%
- Dim to off no
- Power Factor @ Full Load >0.9
- Efficiency @ Full Load ≥78
- THD @ Full Load <12%

Dimmer Compatibility

- Leviton IPE04-1LZ
- Lutron DVELV-300P

As technology changes, please use information above as guidance. For most recent updated information please contact factory. Specifications subject to change without notice.