

DELTALIGHT



M52 - 2 LED OK 82720 MDL

REFERENCE 421 248 2822 MDL





View on website

General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 45° swiveling
INFORMATION	2 x LENS FL-20° EXCL.LED POWER SUPPLY 48V-DC

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	F
CERTIFICATES	CB, EAC, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED array 6W / CRI>80 / 2700K / 558lm)
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	1116lm // 12W // 94lm/W
LED TECHNICS (LUMINAIRE)	948lm // 14W // 69lm/W

Requirements

LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR

For detailed installation instructions, please consult the manual : **421_248_2XXX_MDL_HAND.pdf**

DELTALIGHT

M52 - 2 LED OK 82720 MDL

421 248 2822 MDL


FINISH YOUR SPECIFICATION

Current supply

# of Fixtures

Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



21032 0030 SMART 48 MODULATOR PLUG-IN WD — 14 ☐


Dimtype: WDL = wireless dimmable

SMART 48

# of Fixtures


Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



300 90 011 SMART 48 MODULATOR DIM9 — 14 ☐

Dimtype: 1-10V or DALI or push button



300 90 012 SMART 48 MODULATOR WD — 14 ☐


Dimtype: WDL = wireless dimmable

LED power supplies

# of Fixtures

Min current | Max current


ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



300 89 48 90 LED POWER SUPPLY 48V-DC / 90W — 7 ☐

Dimtype: non-dimmable

Cutout dimension (mm): 75




300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN — 7 ☐

Dimtype: non-dimmable

DELTALIGHT


M52 - 2 LED OK 82720 MDL

421 248 2822 MDL




300 89 48 150 LED POWER SUPPLY 48V-DC / 150W — 11

Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN — 17


Dimtype: non-dimmable



21012 0230 LED POWER SUPPLY 48V-DC / 100W — 7

Dimtype: non-dimmable

Cutout dimension (mm): 40







21012 0240 LED POWER SUPPLY 48V-DC / 200W — 14

Dimtype: non-dimmable

Cutout dimension (mm): 40

COMPATIBLE COMPOSABLES

SPLITLINE M52 profile	Available Colours
 **420 52 10 00** SPM52 - PROFILE 1m	
 **420 52 20 00** SPM52 - PROFILE 2m	
 **420 52 30 00** SPM52 - PROFILE 3m	
 **24413 0000** SPM52 - PROFILE	

M52 - 2 LED OK 82720 MDL

421 248 2822 MDL

Notes: