




## DEEP RINGO DYNAMIC FOCUS TRIMLESS 927

**REFERENCE** 32112 9200 CR

AVAILABLE IN  
**BLACK** 32112 9200 B  
**BRUSHED ALU** 32112 9200 BRA  
**BRUSHED ANTHRACITE** 32112 9200 BRAT  
**BRUSHED BROWN BRONZE** 32112 9200 BRBB  
**BRUSHED COPPER** 32112 9200 BRCU  
**BRUSHED GOLD** 32112 9200 BRG  
**BRUSHED OLD BRONZE** 32112 9200 BROB  
**CREAM** 32112 9200 CR  
**PIANO BLACK** 32112 9200 PB  
**WHITE** 32112 9200 W



[View on website](#)



### General info

|                               |                  |
|-------------------------------|------------------|
| <b>LOCATION</b>               | indoor           |
| <b>INSTALLATION</b>           | Ceiling Recessed |
| <b>CUTOUT SHAPE/SIZE (MM)</b> | round - Ø KIT    |
| <b>INGRESS PROTECTION</b>     | IP20             |
| <b>WEIGHT (KG)</b>            | 0.3              |
| <b>ADJUSTABILITY</b>          | non adjustable   |

### Electrical info

|                     |                           |
|---------------------|---------------------------|
| <b>CLASS</b>        | III                       |
| <b>DIM TYPE</b>     | depending on power supply |
| <b>ENERGY CLASS</b> | G                         |

### Lightsource info

|                                    |                                                                                                                                                                                                                         |
|------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                                                                                                                                                                                                     |
| <b>LIGHTSOURCE</b>                 | 13° (central part only): LED array 5,8W / CRI>90 (R9: 56) / 2700K / 528lm<br>Or<br>24° central part: LED array 1W / CRI>90 (R9: 56) / 2700K / 63lm<br>24° ring part: LED cluster 5,5W / CRI>90 (R9: 50) / 2700K / 868lm |
| <b>SDCM</b>                        | SDCM2<br>SDCM3                                                                                                                                                                                                          |
| <b>RISKGROUP</b>                   | RG2 (threshold 0,6m)<br>RG1                                                                                                                                                                                             |
| <b>LM80</b>                        | L90B10 > 41000<br>L80 > 60000                                                                                                                                                                                           |
| <b>BEAMANGLE</b>                   | 13°-24°                                                                                                                                                                                                                 |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 13° (central part only): 528lm // 5,8W // 94lm/W<br>Or<br>24° central part: 63lm // 1W // 100lm/W<br>24° ring part: 868lm // 5,5W // 158lm/W                                                                            |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 13° (central part only): 475lm // 6,7W // 71lm/W<br>Or<br>24° ring part: 347lm // 6,3W // 55lm/W                                                                                                                        |

### Requirements

MOUNTING KIT R82 TRIMLESS O.F.A.  
 LED POWER SUPPLY DYNAMIC FOCUS

## DEEP RINGO DYNAMIC FOCUS TRIMLESS 927

32112 9200 CR

For detailed installation instructions, please consult the manual : [32112\\_XXX0\\_HAND.pdf](#)

### CEILING COMPATIBILITY

| Ceiling Type                                                                                                         | Mounting Kit                                                                                                                      |          |
|----------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|----------|
|  <b>System ceiling</b>               |  15212 2000 - MOUNTING KIT R82 TRIMLESS O.F.A.   | Required |
|  <b>Plasterboard</b>                 |  15212 2000 - MOUNTING KIT R82 TRIMLESS O.F.A.   | Required |
|  <b>Stucanet</b>                     |  15212 2000 - MOUNTING KIT R82 TRIMLESS O.F.A.   | Required |
|  <b>Concrete + plaster</b>           |  15212 2000 - MOUNTING KIT R82 TRIMLESS O.F.A.   | Required |
|  <b>Lintel + plaster</b>            |  15212 2000 - MOUNTING KIT R82 TRIMLESS O.F.A. | Required |
|  <b>Hollow-core slab + plaster</b> |  15212 2000 - MOUNTING KIT R82 TRIMLESS O.F.A. | Required |
|                                    |  29810 0100 - MOUNTING KIT SIDE AIR ONLY 1     | Required |
|                                                                                                                      |  29810 0050 - MOUNTING KIT NO AIR 101          | Required |
|                                                                                                                      |  29810 0010 - MOUNTING KIT SIDE AIR 101        | Required |
|                                    |  29810 0210 - MOUNTING KIT TOP AIR 101         | Required |
|                                                                                                                      |  29810 0050 - MOUNTING KIT NO AIR 101          | Required |
|                                                                                                                      |  29810 0200 - MOUNTING KIT TOP AIR ONLY 1      | Required |
|  <b>Cold stretched ceiling</b>     |  15212 0070 - MOUNTING KIT R82 TRIMLESS CSC    | Required |
|  <b>Warm stretched ceiling</b>     |  15212 0150 - MOUNTING KIT R82 TRIMLESS WSC    | Required |

### FINISH YOUR SPECIFICATION

#### LED power supplies

#### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current

# DELTALIGHT

## DEEP RINGO DYNAMIC FOCUS TRIMLESS 927

32112 9200 CR




**32110 0015** LED POWER SUPPLY DYNAMIC FOCUS DIM5

3

☐

Dimtype: DALI

Cutout dimension (mm): 75



**32110 0020** LED POWER SUPPLY DYNAMIC FOCUS + WIRELESS CONTROL DIM5


3

☐

Dimtype: DALI

Cutout dimension (mm): 75

### Mounting kits




**15212 2000** MOUNTING KIT R82 TRIMLESS O.F.A.

☐

Cutout dimension (mm): 105

### Mounting kits stretched ceiling



**15212 0070** MOUNTING KIT R82 TRIMLESS CSC

☐

**15212 0150** MOUNTING KIT R82 TRIMLESS WSC

☐

Notes: