



MINIGRID IN TRIMLESS 1 93006

100013 9310 B-B



AVAILABLE IN

BLACK-BLACK 100013 9310 B-B

BLACK-WHITE 100013 9310 B-W

WHITE-BLACK 100013 9310 W-B

WHITE-WHITE 100013 9310 W-W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	rectangle - KIT
RECESSED DEPTH (MM)	85
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.6
ADJUSTABILITY	0° to 20° swiveling, 350° rotatable
INFORMATION	LENS SP-6° EXCL.LED POWER SUPPLY 700-1400mA-DC

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	F
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 2-4,3W / CRI>90 / 3000K / 229-400lm
SDCM	SDCM3
RISKGROUP	RG2 (threshold 0,6m)
BEAMANGLE	6°
LED TECHNICS (LIGHT SOURCE)	400lm // 4,3W // 93lm/W
LED TECHNICS (LUMINAIRE)	366lm // 4,9W // 74lm/W

Requirements

MINIGRID IN 1 MOUNTING KIT

MINIGRID IN 1 MOUNTING KIT LARGE

CONCRETE PACK MGIT 1

LED POWER SUPPLY 700 / 1400mA-DC DIM (Remote)

For detailed installation instructions, please consult the manual : [100013_XXX0_HAND.pdf](#)

DELTALIGHT

MINIGRID IN TRIMLESS 1 93006

100013 9310 B-B

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 System ceiling	 202 71 95 01 - MINIGRID IN 1 MOUNTING KIT	Required
 Plasterboard	 202 71 95 01 - MINIGRID IN 1 MOUNTING KIT	Required
 Stucanet	 202 71 95 01 - MINIGRID IN 1 MOUNTING KIT	Required
	 202 71 95 01L - MINIGRID IN 1 MOUNTING KIT LARGE	Required
 Concrete	 202 71 96 01 - CONCRETE PACK MGIT 1	Required
 Concrete + plaster	 202 71 95 01L - MINIGRID IN 1 MOUNTING KIT LARGE	Required
 Lintel + plaster	 202 71 95 01L - MINIGRID IN 1 MOUNTING KIT LARGE	Required
 Hollow-core slab	 202 71 96 01 - CONCRETE PACK MGIT 1	Required
 Hollow-core slab + plaster	 202 71 95 01L - MINIGRID IN 1 MOUNTING KIT LARGE	Required
 Stretched ceiling	 15212 0120 - MOUNTING KIT MINIGRID IN 1 CSC	Required

FINISH YOUR SPECIFICATION


LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




300 48 700 ED1

LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM1

2->13

Dimtype: 1-10V

Cutout dimension (mm): 30



300 48 700 ED5

LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM5











2->13

Dimtype: DALI

Cutout dimension (mm): 45









MINIGRID IN TRIMLESS 1 93006

100013 9310 B-B

	300 48 700 MDL LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W MDL	2->13	☐
	Dimtype: non-dimmable		
	Cutout dimension (mm): 30		
	300 48 700 PRO ED1 LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W PRO DIM1	2->13	☐
	Dimtype: 1-10V		
	Cutout dimension (mm): 30		
	300 48 700 PRO ED5 LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W PRO DIM5	2->13	☐
	Dimtype: DALI		
	Cutout dimension (mm): 45		
	300 48 700 PRO WDL LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W PRO WDL	2->13	☐
	Dimtype: WDL = wireless dimmable		
	Cutout dimension (mm): 45		
	300 48 700 WDL LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W WDL	2->13	☐
	Dimtype: WDL = wireless dimmable		
	Cutout dimension (mm): 45		
	300 90 61 LED POWER SUPPLY MULTI-POWER DIM6	15 - -	☐
	Dimtype: mains (phase cut-off) or push button		
	Cutout dimension (mm): 56		
	300 90 64 LED POWER SUPPLY MULTI-POWER DIM7	15(6) - -	☐
	Dimtype: 1-10V or push button		
	Cutout dimension (mm): 72		
	300 90 67 LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9	3->14 3->14 -	☐
	Dimtype: 1-10V or DALI or push button		
	300 90 68 LED POWER SUPPLY MULTI-POWER DIM5	2->15(7) - -	☐
	Dimtype: DALI		
	Cutout dimension (mm): 72		
	300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9	29(19) - -	☐
	Dimtype: 1-10V or DALI or push button		
	Cutout dimension (mm): 84		

MINIGRID IN TRIMLESS 1 93006





100013 9310 B-B

	300 90 93 LED POWER SUPPLY 700mA-DC / 17W Dimtype: non-dimmable Cutout dimension (mm): 48	2->8(5) ☐
	300 90 118 LED POWER SUPPLY 700mA-DC / 20W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 55	6->9 ☐
	300 90 123 LED POWER SUPPLY 700mA-DC / 36W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 50	2->17 ☐
	300 90 124 LED POWER SUPPLY MULTI-POWER DIM7 Dimtype: 1-10V or push button Cutout dimension (mm): 55	2->10(7) - - ☐
	300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5 Dimtype: DALI Cutout dimension (mm): 55	2->9(7) - - ☐
	300 90 134 LED POWER SUPPLY MULTI-POWER HV DIM7 Dimtype: 1-10V or push button Cutout dimension (mm): 84	28(18) - - ☐
	300 90 135 LED POWER SUPPLY MULTI-POWER HV Dimtype: non-dimmable Cutout dimension (mm): 90	10->28 9->20 - ☐
	300 90 136 LED POWER SUPPLY MULTI-POWER HC DIM9 Dimtype: 1-10V or DALI or push button Cutout dimension (mm): 90	- 14(12) 13(9) ☐
	300 90 148 LED POWER SUPPLY 1050mA-DC / 22W Dimtype: non-dimmable Cutout dimension (mm): 48	7(3) ☐
	21012 004W LED POWER SUPPLY MULTI-POWER WDL Dimtype: WDL = wireless dimmable Cutout dimension (mm): 84	23(18) 17(11) - ☐


DELTALIGHT

MINIGRID IN TRIMLESS 1 93006


100013 9310 B-B

	21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL	4->17 4->12 -	☐
Dimtype: WDL = wireless dimmable			
Cutout dimension (mm): 54			
	21012 0490 LED POWER SUPPLY 700mA-DC / 30W IP68	2->14(7)	☐
Dimtype: non-dimmable			
Cutout dimension (mm): 60			
	21032 0315 LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM5	2->14	☐
Dimtype: DALI			
Cutout dimension (mm): 30			
	21032 0385 LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W PRO DIM5	2->14	☐
Dimtype: DALI			
Cutout dimension (mm): 30			

Concrete packs

	202 71 96 01 CONCRETE PACK MGIT 1		☐
Cutout dimension (mm): 160 x 160			

Mounting kits


	202 71 95 01 MINIGRID IN 1 MOUNTING KIT		☐
Cutout dimension (mm): 130 x 130			
	202 71 95 01L MINIGRID IN 1 MOUNTING KIT LARGE		☐
Cutout dimension (mm): 200			

DELTALIGHT

MINIGRID IN TRIMLESS 1 93006

100013 9310 B-B

Mounting kits stretched ceiling



15212 0120 MOUNTING KIT MINIGRID IN 1 CSC



Notes: