



OML50 - PRISMATIC LENS DU HO 1640mm 930 DIM5

31635 9305 B

AVAILABLE IN
BLACK 31635 9305 B

 [View on website](#)



General info

| | |
|---------------------------|--|
| LOCATION | indoor |
| INGRESS PROTECTION | IP20 |
| WEIGHT (KG) | 2.4 |
| INFORMATION | INCL.DIMMABLE LED POWER SUPPLY (DALI-2 standard) CABLING 1 CIRCUIT |

Electrical info

| | |
|---------------------|----------------------|
| ELECTRICAL | 220-240V / 0 50-60Hz |
| CLASS | I |
| POWER SUPPLY | YES |
| DIM TYPE | DALI |
| ENERGY CLASS | D |
| CERTIFICATES | EPD, RCM |

Lightsource info

| | |
|------------------------------------|--|
| LIGHTSOURCE NAME | LED |
| LIGHTSOURCE | DOWN: LED cluster 38,8W / CRI>90 (R9: 50) / 3000K / 5950lm UP: LED cluster 30,2W / CRI>90 (R9: 50) / 3000K / 4368lm |
| TM-30 VALUES | Rf: 92 / Rg: 100 |
| SDCM | SDCM3 |
| RISKGROUP | RG1 |
| LM80 | L80 > 60000 |
| LED TECHNICS (LIGHT SOURCE) | DOWN: 5950lm // 38,8W // 153lm/W UP: 4368lm // 30,2W // 145lm/W |

Options

WIRELESS CONTROL DIM5

Notes: