

LOGIC LINEAR 440 92715 DIM5

30817 9215 INOX

AVAILABLE IN
INOX 30817 9215 INOX



[View on website](#)



General info

LOCATION	outdoor
INSTALLATION	Floor Recessed
CUTOUT SHAPE/SIZE (MM)	rectangle - BOX
RECESSED DEPTH (MM)	140
INGRESS PROTECTION	IP67
PROTECTION AGAINST MECHANICAL IMPACT	IK09
WEIGHT (KG)	2.3
ADJUSTABILITY	non adjustable
INFORMATION	8 x LENS SP-15° INCL.DIMMABLE LED POWER SUPPLY 650mA-DC INCL.1 x CABLE H07 RN-F 5 x 1mm ² 0,5m INCL.IP68 CONNECTOR 5P ESG 8mm max.500kg

Electrical info

ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	F
CERTIFICATES	CB, ENEC, EPD, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 14,4W / CRI>90 (R9: 50) / 2700K / 1644lm
TM-30 VALUES	Rf: 91 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 150000
BEAMANGLE	15°
LED TECHNICS (LIGHT SOURCE)	1644lm // 14,4W // 111lm/W
LED TECHNICS (LUMINAIRE)	1217lm // 16,6W // 73lm/W

Requirements

LOGIC LINEAR BOX

For detailed installation instructions, please consult the manual : [30817_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Ground mounting boxes




30810 0010 LOGIC LINEAR 440 BOX

☐

Cutout dimension (mm): 480 x 150

Waterproof connection parts



21034 0150 IP68 Y-CONNECTOR 5P

☐

Notes: