



OML50 - PRISMATIC LENS DU HO 1640mm 930 DIM5

31635 9305 B

BESCHIKBAAR IN
ZWART 31635 9305 B



[Bekijk op website](#)



Algemene info	
LOCATIE	binnen
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	2.4
INFO	INCL.DIMMABLE LED POWER SUPPLY (DALI-2 standard) CABLING 1 CIRCUIT
Elektrische info	
ELEKTRISCH	220-240V / 0 50-60Hz
KLASSE	I
VOEDING INBEGREPEN	YES
DIM TYPE	DALI
ENERGIE KLASSE	D
CERTIFICATES	EPD, RCM
Info lichtbron	
LIGHTSOURCE NAME	LED
LICHTBRON	DOWN: LED cluster 38,8W / CRI>90 (R9: 50) / 3000K / 5950lm UP: LED cluster 30,2W / CRI>90 (R9: 50) / 3000K / 4368lm
TM-30 WAARDEN	Rf: 92 / Rg: 100
SMD	SDCM3
RISK-GROEP	RG1
LM80	L80 > 60000
LED TECHNIEK (LICHTBRON)	DOWN: 5950lm // 38,8W // 153lm/W UP: 4368lm // 30,2W // 145lm/W

Opties	
WIRELESS CONTROL DIM5	

Notes: