



Image may differ from the actual product
Consult drawing for correct size

SUPERLOOP HC 170 SBL 927

321 117 92 FG



AVAILABLE IN

BLACK 321 117 92 B

FLEMISH BRONZE 321 117 92 FBR

FLEMISH GOLD 321 117 92 FG

WHITE 321 117 92 W



[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	5.5
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL EXCL.LED POWER SUPPLY 1200-1700mA-DC INCL.3 x CABLE SUSPENSION SINGLE AUTO. 3.0m INCL.1 x CABLE 2 x 0.75mm ²
Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, EAC, ENEC, EPD
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 51,7-71,4W / CRI>90 (R9: 59) / 2700K / 7128-9460lm
SDCM	SDCM3
LM80	L70 > 30000
LED TECHNICS (LIGHT SOURCE)	9460lm // 71,4W // 132lm/W
LED TECHNICS (LUMINAIRE)	5685lm // 82,1W // 69lm/W

Requirements

LED POWER SUPPLY 1200 / 1700mA-DC DIM
SUPERLOOP POWERBOX H 1200mA
SUPERLOOP POWERBOX H 1700mA


Options

CABLE BASE R / S
COVERSET R 62-90-100 / S 62-80-90
CONNECTION ST / CONNECTION TRIMLESS
SUSPENSION ST / SUSPENSION TRIMLESS

For detailed installation instructions, please consult the manual : [321_X17_93_HAND.pdf](#)



FINISH YOUR SPECIFICATION

Current supply

	203 99 55 ANO CABLE BASE R ANO	☐
	203 99 55 B CABLE BASE R B	☐
	203 99 55 W CABLE BASE R W	☐
	203 99 56 ANO CABLE BASE S ANO	☐
	203 99 56 B CABLE BASE S B	☐
	203 99 56 W CABLE BASE S W	☐

Power box



of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
	321 55 312 ED1 B SUPERLOOP POWERBOX H8 1200mA DIM1 B	1 ☐
	321 55 312 ED1 W SUPERLOOP POWERBOX H8 1200mA DIM1 W	1 ☐
	321 55 312 ED5 B SUPERLOOP POWERBOX H 1200mA DIM5 B	1 ☐
	321 55 312 ED5 W SUPERLOOP POWERBOX H 1200mA DIM5 W	1 ☐

DELTALIGHT

SUPERLOOP HC 170 SBL 927

321 117 92 FG





	<u>321 55 317 ED1 B</u> SUPERLOOP POWERBOX H8 1700mA DIM1 B	1	☐
	<u>321 55 317 ED1 W</u> SUPERLOOP POWERBOX H8 1700mA DIM1 W	1	☐
	<u>20548 0025 B</u> SUPERLOOP POWERBOX H9 1200mA DIM5 B	1	☐
	<u>20548 0025 W</u> SUPERLOOP POWERBOX H9 1200mA DIM5 W	1	☐

LED power supplies

of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current






	<u>300 90 130</u> LED POWER SUPPLY 1200mA-DC / 60W DIM5	1	☐
	Dimtype: DALI		
	Cutout dimension (mm): 95		
	<u>300 90 132</u> LED POWER SUPPLY 1200mA-DC / 70W DIM1	1	☐
	Dimtype: 1-10V		
	Cutout dimension (mm): 80		
	<u>300 90 133</u> LED POWER SUPPLY 1700mA-DC / 99W DIM1	1	☐
	Dimtype: 1-10V		
	Cutout dimension (mm): 80		
	<u>21012 0475</u> LED POWER SUPPLY 1700mA-DC / 92W DIM5	1	☐
	Dimtype: DALI		

DELTALIGHT

SUPERLOOP HC 170 SBL 927

321 117 92 FG

Coversets


	<u>204 00 62 ANO</u>	COVERSET R 62 ANO	☐
	<u>204 00 62 B</u>	COVERSET R 62 B	☐
	<u>204 00 62 W</u>	COVERSET R 62 W	☐
	<u>204 00 90 ANO</u>	COVERSET R 90 ANO	☐
	<u>204 00 90 B</u>	COVERSET R 90 B	☐
	<u>204 00 90 W</u>	COVERSET R 90 W	☐
	<u>204 00 100 ANO</u>	COVERSET R 100 ANO	☐
	<u>204 00 100 B</u>	COVERSET R 100 B	☐
	<u>204 00 100 W</u>	COVERSET R 100 W	☐
	<u>204 62 62 ANO</u>	COVERSET S 62 ANO	☐
	<u>204 62 62 B</u>	COVERSET S 62 B	☐
	<u>204 62 62 W</u>	COVERSET S 62 W	☐
	<u>204 80 80 ANO</u>	COVERSET S 80 ANO	☐
	<u>204 80 80 B</u>	COVERSET S 80 B	☐

DELTALIGHT

SUPERLOOP HC 170 SBL 927

321 117 92 FG

204 80 80 W COVERSET S 80 W



204 90 90 ANO COVERSET S 90 ANO




204 90 90 B COVERSET S 90 B



204 90 90 W COVERSET S 90 W




Suspension parts



328 10 01 SUSPENSION TRIMLESS O.F.A.



Cutout dimension (mm): 62 (CONCRETE: 102)



15225 0340 B SUSPENSION ST B




Cutout dimension (mm): 27

15225 0340 W SUSPENSION ST W



Electric connection parts



328 10 03 CONNECTION TRIMLESS O.F.A.



Cutout dimension (mm): 62 (CONCRETE: 102)



15225 0360 B CONNECTION ST B



Cutout dimension (mm): 43

15225 0360 W CONNECTION ST W



DELTALIGHT

SUPERLOOP HC 170 SBL 927

321 117 92 FG

Notes: