

SPY 39 PLUG FOCUS 930

24176 9300 FW

AVAILABLE IN

BLACK 24176 9300 B

BRUSHED ALU 24176 9300 BRA

BRUSHED ANTHRACITE 24176 9300 BRAT

BRUSHED COPPER 24176 9300 BRCU

BRUSHED GOLD 24176 9300 BRG

BRUSHED OLD BRONZE 24176 9300 BROB

FLEMISH BRONZE 24176 9300 FBR

FLEMISH GOLD 24176 9300 FG

FULL WHITE 24176 9300 FW

GOLD COLOURED 24176 9300 GC

WHITE 24176 9300 W



[View on website](#)



General info

| | |
|-------------------------------|-------------------------------------|
| LOCATION | indoor |
| INSTALLATION | Ceiling Semi-recessed |
| CUTOUT SHAPE/SIZE (MM) | round - Ø KIT |
| RECESSED DEPTH (MM) | 80 |
| INGRESS PROTECTION | IP20 |
| WEIGHT (KG) | 0.4 |
| ADJUSTABILITY | 0° to 85° swiveling, 355° rotatable |
| INFORMATION | ADJUSTABLE BEAM 15°-45° |

Electrical info

| | |
|---------------------|---------------------------|
| CLASS | III |
| DIM TYPE | depending on power supply |
| ENERGY CLASS | E |
| CERTIFICATES | CB, ENEC |

Lightsource info

| | |
|------------------------------------|-----------------------------------------------------------|
| LIGHTSOURCE NAME | LED |
| LIGHTSOURCE | LED array 5,8-8,6W / CRI>90 (R9: 52) / 3000K / 734-1018lm |
| TM-30 VALUES | rf: 90 / Rg: 99 |
| SDCM | SDCM1 |
| RISKGROUP | RG1 |
| LM80 | L90B10 > 50000 |
| BEAMANGLE | 15°-45° |
| LED TECHNICS (LIGHT SOURCE) | 1018lm // 8,6W // 118lm/W |
| LED TECHNICS (LUMINAIRE) | 303lm // 9,9W // 31lm/W |

Requirements

MOUNTING KIT PLUG O.F.A.

LED POWER SUPPLY 350 / 500mA-DC DIM

DELTALIGHT

SPY 39 PLUG FOCUS 930

24176 9300 FW

For detailed installation instructions, please consult the manual : [24176_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY

| Ceiling Type | Mounting Kit | |
|--------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------|----------|
|  Plasterboard |  24144 0060 - MOUNTING KIT PLUG O.F.A. | Required |
|  Concrete + plaster |  24144 0060 - MOUNTING KIT PLUG O.F.A. | Required |
|  Lintel + plaster |  24144 0060 - MOUNTING KIT PLUG O.F.A. | Required |
|  Hollow-core slab + plaster |  24144 0060 - MOUNTING KIT PLUG O.F.A. | Required |

FINISH YOUR SPECIFICATION


LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




300 48 350 ED1 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1

2

Dimtype: 1-10V

Cutout dimension (mm): 30




300 48 350 ED5 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

2

Dimtype: DALI

Cutout dimension (mm): 45




300 48 350 MDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL

2

Dimtype: non-dimmable

Cutout dimension (mm): 30



300 48 350 WDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL

2

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45

DELTALIGHT

SPY 39 PLUG FOCUS 930

24176 9300 FW



300 48 500 ED1 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1

2

Dimtype: 1-10V

Cutout dimension (mm): 30



300 48 500 ED5 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5

2

Dimtype: DALI

Cutout dimension (mm): 45



300 48 500 MDL LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W MDL

2

Dimtype: non-dimmable

Cutout dimension (mm): 30



300 48 500 WDL LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W WDL

2

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45



300 90 61 LED POWER SUPPLY MULTI-POWER DIM6

2 | 2

Dimtype: mains (phase cut-off) or push button

Cutout dimension (mm): 56



300 90 63 LED POWER SUPPLY MULTI-POWER DIM9

4(4) | 4(4)

Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 82



300 90 64 LED POWER SUPPLY MULTI-POWER DIM7

2(2) | 2(1)

Dimtype: 1-10V or push button

Cutout dimension (mm): 72



300 90 67 LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9

2 | -

Dimtype: 1-10V or DALI or push button




300 90 68 LED POWER SUPPLY MULTI-POWER DIM5

2(2) | 2(1)

Dimtype: DALI

Cutout dimension (mm): 72



300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9

2->6(6) | 6(4)

Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 84

DELTALIGHT

SPY 39 PLUG FOCUS 930

24176 9300 FW



300 90 124 LED POWER SUPPLY MULTI-POWER DIM7

2(2) | 2(1)



Dimtype: 1-10V or push button

Cutout dimension (mm): 55



300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5

2(2) | 2(1)



Dimtype: DALI

Cutout dimension (mm): 55



300 90 135 LED POWER SUPPLY MULTI-POWER HV

3->4 | 2->4



Dimtype: non-dimmable

Cutout dimension (mm): 90




21012 0010 LED POWER SUPPLY MULTI POWER

2 | 2



Dimtype: non-dimmable

Cutout dimension (mm): 50



21012 0021 LED POWER SUPPLY MULTI POWER DIM1

3 | 3



Dimtype: 1-10V

Cutout dimension (mm): 54




21012 0035 LED POWER SUPPLY MULTI POWER DIM5

3 | 3



Dimtype: DALI

Cutout dimension (mm): 54




21012 004W LED POWER SUPPLY MULTI-POWER WDL

4(4) | 3(3)



Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 84




21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL

3 | 3



Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 54




21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8

2->2 | 2->2



Dimtype: mains (phase cut-off)

Cutout dimension (mm): 50



21012 0278 LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8

1



Dimtype: mains (phase cut-off)

Cutout dimension (mm): 55

DELTALIGHT

SPY 39 PLUG FOCUS 930

24176 9300 FW



21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8

2->3

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 55



21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8

2 | 2

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 48



21012 0308 LED POWER SUPPLY 350mA / 7,35W DIM8

1

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 40




21012 0318 LED POWER SUPPLY 500mA / 10W DIM8

1

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 40




21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68

2(2)

Dimtype: non-dimmable

Cutout dimension (mm): 60



21012 0500 LED POWER SUPPLY 500mA-DC / 24W IP68

2(1)

Dimtype: non-dimmable

Cutout dimension (mm): 60




21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

2

Dimtype: DALI

Cutout dimension (mm): 30




21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5

2

Dimtype: DALI

Cutout dimension (mm): 30

Mounting kits



24144 0060 MOUNTING KIT PLUG O.F.A.

Cutout dimension (mm): 62 (CONCRETE: 102)

DELTALIGHT

SPY 39 PLUG FOCUS 930

24176 9300 FW

Notes: