
DELTALIGHT




# DOT.COM M4 ST OK 92714

**REFERENCE** 424 222 04 921 B-B

AVAILABLE IN
**BLACK-BLACK** 424 222 04 921 B-B
**BLACK-CHROMED** 424 222 04 921 B-C
**BLACK-FLEMISH GOLD** 424 222 04 921 B-FG
**WHITE-BLACK** 424 222 04 921 W-B
**WHITE-CHROMED** 424 222 04 921 W-C
**WHITE-FLEMISH GOLD** 424 222 04 921 W-FG




View on website

| General info | |
|---|---|
| **LOCATION** | indoor |
| **INSTALLATION** | Ceiling Recessed |
| **CUTOUT SHAPE/SIZE (MM)** | rectangle - 136 x 40 |
| **RECESSED DEPTH (MM)** | 58 |
| **THICKNESS OF MOUNTING SURFACE (MM)** | max.25 |
| **INGRESS PROTECTION** | IP20 |
| **WEIGHT (KG)** | 0.3 |
| **ADJUSTABILITY** | 30° swiveling |
| **INFORMATION** | 4 x REFLECTOR SP-14°<br>EXCL.LED POWER SUPPLY 500mA-DC |

| Electrical info | |
|---|---|
| **CLASS** | III |
| **DIM TYPE** | depending on power supply |
| **ENERGY CLASS** | E |
| **CERTIFICATES** | CB, EAC, ENEC, LCA |

| Lightsource info | |
|---|---|
| **LIGHTSOURCE NAME** | LED |
| **LIGHTSOURCE** | LED cluster 5,7W / CRI>90 (R9: 50) / 2700K / 631lm |
| **TM-30 VALUES** | Rf: 92 / Rg: 100 |
| **SDCM** | SDCM3 |
| **RISKGROUP** | RG2 |
| **LM80** | L80 > 60000 |
| **BEAMANGLE** | 14° |
| **LED TECHNICS (LIGHT SOURCE)** | 631lm // 5,7W // 111lm/W |
| **LED TECHNICS (LUMINAIRE)** | 461lm // 6,6W // 70lm/W |

**Requirements**

LED POWER SUPPLY 500mA-DC DIM

For detailed installation instructions, please consult the manual : **424_222_04_XXX_HAND.pdf**

DELTALIGHT

# DOT.COM M4 ST OK 92714

424 222 04 921 B-B

## CEILING COMPATIBILITY

| Ceiling Type | Mounting Kit |
|---|---|
|  System ceiling | - |
|  Plasterboard | - |
|  Stucanet | - |
|  Wood | - |
|  Stretched ceiling | - |


## FINISH YOUR SPECIFICATION

### LED power supplies

### # of Fixtures

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


**Min current | Max current**




**300 48 500 ED1** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1 — 3 ☐

**Dimtype: 1-10V**


**Cutout dimension (mm): 30**




**300 48 500 ED5** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5 — 3 ☐

**Dimtype: DALI**


**Cutout dimension (mm): 45**




**300 48 500 MDL** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W MDL — 3 ☐

**Dimtype: non-dimmable**

**Cutout dimension (mm): 30**





**300 48 500 WDL** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W WDL — 3 ☐

**Dimtype: WDL = wireless dimmable**

**Cutout dimension (mm): 45**

# DOT.COM M4 ST OK 92714


424 222 04 921 B-B




**300 90 61** LED POWER SUPPLY MULTI-POWER DIM6 — 4

**Dimtype: mains (phase cut-off) or push button**


**Cutout dimension (mm): 56**




**300 90 63** LED POWER SUPPLY MULTI-POWER DIM9 — 6(6)

**Dimtype: 1-10V or DALI or push button**


**Cutout dimension (mm): 82**




**300 90 64** LED POWER SUPPLY MULTI-POWER DIM7 — 4(2)

**Dimtype: 1-10V or push button**


**Cutout dimension (mm): 72**




**300 90 68** LED POWER SUPPLY MULTI-POWER DIM5 — 4(2)

**Dimtype: DALI**


**Cutout dimension (mm): 72**




**300 90 69** LED POWER SUPPLY MULTI-POWER HV DIM9 — 9(7)

**Dimtype: 1-10V or DALI or push button**


**Cutout dimension (mm): 84**




**300 90 124** LED POWER SUPPLY MULTI-POWER DIM7 — 3(2)

**Dimtype: 1-10V or push button**


**Cutout dimension (mm): 55**




**300 90 125** LED POWER SUPPLY MULTI-POWER MINI DIM5 — 3(2)

**Dimtype: DALI**


**Cutout dimension (mm): 55**




**300 90 135** LED POWER SUPPLY MULTI-POWER HV — 3->7

**Dimtype: non-dimmable**


**Cutout dimension (mm): 90**




**21012 0010** LED POWER SUPPLY MULTI POWER — 3

**Dimtype: non-dimmable**

**Cutout dimension (mm): 50**




**21012 0021** LED POWER SUPPLY MULTI POWER DIM1 — 4


**Dimtype: 1-10V**

**Cutout dimension (mm): 54**

DELTALIGHT

# DOT.COM M4 ST OK 92714


424 222 04 921 B-B




**21012 0035** LED POWER SUPPLY MULTI POWER DIM5 — 4

**Dimtype: DALI**


**Cutout dimension (mm): 54**




**21012 004W** LED POWER SUPPLY MULTI-POWER WDL — 6(6)

**Dimtype: WDL = wireless dimmable**


**Cutout dimension (mm): 84**




**21012 005W** LED POWER SUPPLY MULTI-POWER COMPACT WDL — 4

**Dimtype: WDL = wireless dimmable**


**Cutout dimension (mm): 54**




**21012 0278** LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8 — 2->2

**Dimtype: mains (phase cut-off)**


**Cutout dimension (mm): 55**




**21012 0288** LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8 — 3->4

**Dimtype: mains (phase cut-off)**


**Cutout dimension (mm): 55**




**21012 0298** LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 — 3

**Dimtype: mains (phase cut-off)**

**Cutout dimension (mm): 48**




**21032 0305** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5 — 3

**Dimtype: DALI**

**Cutout dimension (mm): 30**

Notes: