INFORM R



Who says light for the workplace needs to be boring? Inform R enables you to bring a touch of creativity into the clean and straight lines of the contemporary office environment. Inform R is a family of atypical shapes which are still compliant with the EN 12464, the standard for office lighting.

Specification	
Aperture:	5/8"
Installation method:	4" junction box
Adjustability:	Fixed
Rating:	Damp

Performance	
CRI:	90
SDCM:	3
LED Maintenance:	L80>60,000h

*Power	Down	Up (Optional)
Standard Power:	26.3W	13.2W

Delivered Lumens	2700K (Down/Up)	3000K (Down/Up)	3500K (Down/Up)
Inform R Down:	2886	2926	2998
Inform R Down-Up:	2761/1106	2800/1121	2868/1149

Listing
ETL certified to US and Canadian safety standards.

Warranty
5-year limited warranty.

Ordering
ALL BOXES MUST BE FILLED IN TO CORRECTLY ORDER

Example: INFR07-SPDN30-FG-B-ONSPB-RMTD1-UNV

Luminaire	Shape	Size	Downlight*	Uplight*	CCT	Finish	Style	Installation	Hardware Finish[2]	Application	Controls***
INF INFORM	**R** Round	**07** 777mm / 30 19/32"	**SP** Standard Power	**DN** Downlight only 71°, no uplight **DU**[1] Downlight 71° with uplight added	**27** 2700K **30** 3000K **35** 3500K	**B-B** Black-Black **B-FG** Black-Flemish Gold **FG-B** Flemish Gold-Black **W-B** White-Black **W-W** White-White	**ON**[1] Surface mount **PC** Pendant, 4 suspension points	**SP** Round coverplate for 4" junction box **PR** Round coverplate for 4" junction box	**B** Black **W** White	**RMT**[3] Remote Power Supply	**D1-UNV** 0-10V dim 120-277V


1 DU down-up not available in surface mount (Style ON).
2 Applies to Installation SP & PR (coverplate).
3 Remote power supplies are sized to power one luminaire, including down/up.
*** Contact factory for Dali, DMX, or other dimming options.

Related Products

M-Inform (mounts to recessed, surface, or suspended low voltage system), Inform SQ (linear), Conform, Lass-Oh, Lass-Oh L (linear)

Finish Options

INFORM R ON




BLACK-BLACK



BLACK-FLEMISH GOLD


FLEMISH GOLD-BLACK


WHITE-BLACK


WHITE-WHITE

INFORM R PENDANT




BLACK-BLACK


BLACK-FLEMISH GOLD


FLEMISH GOLD-BLACK


WHITE-BLACK


WHITE-WHITE

FINISH DETAIL


BLACK-BLACK


BLACK-FLEMISH GOLD


FLEMISH GOLD-BLACK



WHITE-BLACK

WHITE-WHITE


UPLIGHT DETAIL


Photometric Data

INFORM R DOWN



71°
downlight

INFORM R DOWN-UP




71°
downlight,
symmetrical uplight

Installation Options


REMOTE DRIVER

A: 8″ x **B:** 2″-3/16 x **C:** 4″-1/4
A: 203mm x **B:** 72mm x **C:** 108mm

- For Remote application
- ETL Listed
- Damp rated




SP - COVERPLATE R 129



BLACK or WHITE
Requires 4" junction box

Included for STYLE ON

PR - COVERPLATE R 212



BLACK or WHITE
Requires 4" junction box

Included for STYLE PC

Driver Options

D1

- Dimming Control 0-10V
- Dimming Range 1-100%
- Dim to off yes at 0.7mA
- Power Factor @ Full Load >0.9
- Efficiency @ Full Load ≥87
- THD @ Full Load <20%
- Title 24 Compliant

Dimmer Compatibility

- Leviton IP710-DLZ
- Lutron DVTV-XX
- WattStopper ADF-120277
- Synergy Lighting Controls ISD BC

As technology changes, please use information above as guidance. For most recent updated information please contact factory. Specifications subject to change without notice.