
DELTALIGHT




LOGIC LINEAR 440 93040 DIM5

REFERENCE 30817 9335 INOX

AVAILABLE IN
INOX 30817 9335 INOX





View on website

General info	
LOCATION	outdoor
INSTALLATION	Floor Recessed
CUTOUT SHAPE/SIZE (MM)	rectangle - BOX
RECESSED DEPTH (MM)	140
INGRESS PROTECTION	IP67
PROTECTION AGAINST MECHANICAL IMPACT	IK09
WEIGHT (KG)	2.3
ADJUSTABILITY	non adjustable
INFORMATION	8 x LENS WFL-40° INCL.DIMMABLE LED POWER SUPPLY 650mA-DC INCL.1 x CABLE H07 RN-F 5 x 1mm² 0,5m INCL.IP68 CONNECTOR 5P ESG 8mm max.500kg

Electrical info	
ELECTRICAL	220-240V / 0|50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 14,4W / CRI>90 (R9: 64) / 3000K / 1798lm
TM-30 VALUES	Rf: 92 / Rg: 99
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 150000
BEAMANGLE	40°
LED TECHNICS (LIGHT SOURCE)	1798lm // 14,4W // 121lm/W
LED TECHNICS (LUMINAIRE)	1200lm // 17W // 72lm/W

Requirements

LOGIC LINEAR BOX

For detailed installation instructions, please consult the manual : **30817_XXX5_HAND.pdf**

DELTALIGHT

LOGIC LINEAR 440 93040 DIM5

30817 9335 INOX

FINISH YOUR SPECIFICATION


Ground mounting boxes



30810 0010 LOGIC LINEAR 440 BOX ☐

Cutout dimension (mm): 480 x 150

Waterproof connection parts



21034 0150 IP68 Y-CONNECTOR 5P ☐

Notes: