
DELTALIGHT



# DEEP RINGO DYNAMIC FOCUS 927

**REFERENCE** 32111 9200 BRCU

AVAILABLE IN
**BLACK** 32111 9200 B
**BRUSHED ALU** 32111 9200 BRA
**BRUSHED ANTHRACITE** 32111 9200 BRAT
**BRUSHED BROWN BRONZE** 32111 9200 BRBB
**BRUSHED COPPER** 32111 9200 BRCU
**BRUSHED GOLD** 32111 9200 BRG
**BRUSHED OLD BRONZE** 32111 9200 BROB
**CREAM** 32111 9200 CR
**PIANO BLACK** 32111 9200 PB
**WHITE** 32111 9200 W




View on website

| General info | |
|---|---|
| **LOCATION** | indoor |
| **INSTALLATION** | Ceiling Recessed |
| **CUTOUT SHAPE/SIZE (MM)** | round - 76 |
| **THICKNESS OF MOUNTING SURFACE (MM)** | xxxx |
| **INGRESS PROTECTION** | IP20 |
| **WEIGHT (KG)** | 0.3 |
| **ADJUSTABILITY** | non adjustable |

| Electrical info | |
|---|---|
| **CLASS** | III |
| **DIM TYPE** | depending on power supply |
| **ENERGY CLASS** | G |

| Lightsource info | |
|---|---|
| **LIGHTSOURCE NAME** | LED |
| **LIGHTSOURCE** | 13° (central part only): LED array 5,8W / CRI>90 (R9: 56) / 2700K / 528lm<br>Or<br>24° central part: LED array 1W / CRI>90 (R9: 56) / 2700K / 63lm<br>24° ring part: LED cluster 5,5W / CRI>90 (R9: 50) / 2700K / 868lm |
| **SDCM** | SDCM2<br>SDCM3 |
| **RISKGROUP** | RG2 (threshold 0,6m)<br>RG1 |
| **LM80** | L90B10 > 41000<br>L80 > 60000 |
| **BEAMANGLE** | 13°-24° |
| **LED TECHNICS (LIGHT SOURCE)** | 13° (central part only): 528lm // 5,8W // 94lm/W<br>Or<br>24° central part: 63lm // 1W // 100lm/W<br>24° ring part: 868lm // 5,5W // 158lm/W |
| **LED TECHNICS (LUMINAIRE)** | 13° (central part only): 475lm // 7W // 71lm/W<br>Or<br>24° ring part: 347lm // 6W // 55lm/W |

**Requirements**

LED POWER SUPPLY DYNAMIC FOCUS

DELTALIGHT

# DEEP RINGO DYNAMIC FOCUS 927

32111 9200 BRCU

For detailed installation instructions, please consult the manual : **32111_XXX0_HAND.pdf**


## FINISH YOUR SPECIFICATION

### LED power supplies

### # of Fixtures

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


**Min current | Max current**



**32110 0015** LED POWER SUPPLY DYNAMIC FOCUS DIM5 — 3 ☐

**Dimtype: DALI**

**Cutout dimension (mm): 75**



**32110 0020** LED POWER SUPPLY DYNAMIC FOCUS + WIRELESS CONTROL DIM5 — 3 ☐

**Dimtype: DALI**

**Cutout dimension (mm): 75**

Notes: