





PUNK 452 C 93040 DIM8

471 222 932 ED8 B

AVAILABLE IN
BLACK 471 222 932 ED8 B
GOLD COLOURED 471 222 932 ED8 GC



 [View on website](#)




General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	1
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR WFL-40° INCL.DIMMABLE LED POWER SUPPLY 350mA-DC INCL.1 x CABLE SUSPENSION SINGLE AUTO. 1.6m INCL.1 x CABLE 2 x 0.75mm ²
Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	F
CERTIFICATES	CB, EAC, ENEC, RCM
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 6,4W / CRI>90 / 3000K / 587lm
SDCM	SDCM2
RISKGROUP	RG1
BEAMANGLE	40°
LED TECHNICS (LIGHT SOURCE)	587lm // 6,4W // 92lm/W
LED TECHNICS (LUMINAIRE)	488lm // 7,4W // 66lm/W

Requirements	
MIDISPY TUBE	
Options	
SUSPENSION + CONNECTION TRIMLESS	
COVERSET R 90-100	

For detailed installation instructions, please consult the manual : [471 222 XXX ED8 HAND.pdf](#)

FINISH YOUR SPECIFICATION

Miscellaneous control equipment




300 90 004 ED8 WIRELESS CONTROL DIM8

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 40

☐

Coversets




204 00 90 ANO COVERSET R 90 ANO

☐

204 00 90 B COVERSET R 90 B

☐

204 00 90 W COVERSET R 90 W

☐

204 00 100 ANO COVERSET R 100 ANO

☐


204 00 100 B COVERSET R 100 B

☐

204 00 100 W COVERSET R 100 W

☐

Suspension parts



328 10 02 SUSPENSION + CONNECTION TRIMLESS O.F.A.

Cutout dimension (mm): 62 (CONCRETE: 102)


☐

DELTALIGHT

PUNK 452 C 93040 DIM8

471 222 932 ED8 B

Finish your product

	<u>414 03 00 B</u>	MIDISPY TUBE B	☐
	<u>414 03 00 FBR</u>	MIDISPY TUBE FBR	☐
	<u>414 03 00 FG</u>	MIDISPY TUBE FG	☐
	<u>414 03 00 MMAT</u>	MIDISPY TUBE MMAT	☐
	<u>414 03 00 SG</u>	MIDISPY TUBE SG	☐
	<u>414 03 00 W</u>	MIDISPY TUBE W	☐

Notes: