



OML50 - PRISMATIC LENS DU HO 1640mm 940 DIM5

31635 9405 B

BESCHIKBAAR IN
ZWART 31635 9405 B



[Bekijk op website](#)



Algemene info

LOCATIE	binnen
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	2.4
INFO	INCL.DIMMABLE LED POWER SUPPLY (DALI-2 standard) CABLING 1 CIRCUIT

Elektrische info

INGANGSSPANNING	220-240V / 0 50-60Hz
KLASSE	I
VOEDING	YES
DIM TYPE	DALI
ENERGIE KLASSE	D
CERTIFICATEN	EPD, RCM

Info lichtbron

LIGHTSOURCE NAME	LED
LICHTBRON	DOWN: LED cluster 38,8W / CRI>90 (R9: 50) / 4000K / 6062lm UP: LED cluster 30,2W / CRI>90 (R9: 50) / 4000K / 4552lm
TM-30-15 WAARDEN	Rf: 90 / Rg: 101
SDCM	SDCM3
RISK-GROEP	RG1
LM80	L80 > 60000
LED TECHNIEK (LICHTBRON)	DOWN: 6062lm // 38,8W // 160lm/W UP: 4552lm // 30,2W // 151lm/W

Opties

WIRELESS CONTROL DIM5

Notes: