DELTALIGHT



OML50 - PRISMATIC LENS DU HO 1640mm 940 DIM5

REFERENCE 31635 9405 B

AVAILABLE IN
BLACK 31635 9405 B

View on website

General info	
LOCATION	indoor
INGRESS PROTECTION	IP20
WEIGHT (KG)	2.4
INFORMATION	INCL.DIMMABLE LED POWER SUPPLY (DALI-2 standard) CABLING 1 CIRCUIT

Electrical info	
ELECTRICAL	220-240V / 0|50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	D
CERTIFICATES	EPD, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN: LED cluster 38,8W / CRI>90 (R9: 50) / 4000K / 6062lm UP: LED cluster 30,2W / CRI>90 (R9: 50) / 4000K / 4552lm
TM-30 VALUES	Rf: 90 / Rg: 101
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	DOWN: 6062lm // 38,8W // 160lm/W UP: 4552lm // 30,2W // 151lm/W

Options

WIRELESS CONTROL DIM5

Notes: