



INFORM SQ P475-9 DOWN 92767

25572 9220 W-W



AVAILABLE IN

NOIR-NOIR 25572 9220 B-B

NOIR-FLEMISH GOLD 25572 9220 B-FG

BLANC-NOIR 25572 9220 W-B

BLANC-BLANC 25572 9220 W-W



[View on website](#)



General info

LOCATION	interieur
INSTALLATION	Plafond Suspendu
INGRESS PROTECTION	IP20
WEIGHT (KG)	2.9
ADJUSTABILITY	non réglable
INFORMATION	108 x REFLECTOR FL-67° EXCL.LED POWER SUPPLY 900/1350mA-DC INCL.4 x CABLE SUSPENSION SINGLE AUTO. 1,6m INCL.1 x CABLE 2 x 0.75mm ²

Electrical info

CLASS	III
DIM TYPE	selon le type d'alimentation externe
ENERGY CLASS	E
CERTIFICATION	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	3 x (LED cluster 10,5-16,7W / CRI>90 (R9: 50) / 2700K / 1519-2196lm)
RVALUES	Rf: 93 / Rg: 100
SDMC	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
BEAMANGLE	67°
LED TECHNICS (LIGHT SOURCE)	6588lm // 50,1W // 131lm/W
LED TECHNICS (LUMINAIRE)	5751lm // 57,6W // 100lm/W

Requirements

INFORM POWER SUPPLY 60W

INFORM SQ POWERBOX L 75W

Options

CABLE BASE R / S

COVERSET R 62-90-100 / S 62-80-90


CONNECTION ST / CONNECTION TRIMLESS

SUSPENSION ST / SUSPENSION TRIMLESS

For detailed installation instructions, please consult the manual : [25572_XXX0_HAND.pdf](#)



FINISH YOUR SPECIFICATION

le cable d'alimentation

	203 99 55 ANO CABLE BASE R ANO	☐
	203 99 55 B CABLE BASE R B	☐
	203 99 55 W CABLE BASE R W	☐
	203 99 56 ANO CABLE BASE S ANO	☐
	203 99 56 B CABLE BASE S B	☐
	203 99 56 W CABLE BASE S W	☐

les alimentations led

of Fixtures

 web2print_power_supply_info_box		Min current Max current
	25510 0405 INFORM POWER SUPPLY 60W DIM5 Dimtype: DALI	1 ☐
	25510 0450 INFORM POWER SUPPLY 60W Dimtype: non dimmable	1 ☐

DELTALIGHT

INFORM SQ P475-9 DOWN 92767


25572 9220 W-W

Power box

of Fixtures

 web2print_power_supply_info_box

Min current | Max current




25510 0500 B INFORM SQ POWERBOX L 75W B

1

Dimtype: non dimmable

25510 0500 W INFORM SQ POWERBOX L 75W W

1



25510 0515 B INFORM SQ POWERBOX L 75W DIM5 B


1

Dimtype: DALI

25510 0515 W INFORM SQ POWERBOX L 75W DIM5 W

1


les sets pour recouvrement plafond



204 00 62 ANO COVERSET R 62 ANO

204 00 62 B COVERSET R 62 B


204 00 62 W COVERSET R 62 W



204 00 90 ANO COVERSET R 90 ANO

204 00 90 B COVERSET R 90 B

204 00 90 W COVERSET R 90 W






204 00 100 ANO COVERSET R 100 ANO



DELTALIGHT

INFORM SQ P475-9 DOWN 92767

25572 9220 W-W

	<u>204 00 100 B</u>	COVERSET R 100 B	☐
	<u>204 00 100 W</u>	COVERSET R 100 W	☐
	<u>204 62 62 ANO</u>	COVERSET S 62 ANO	☐
	<u>204 62 62 B</u>	COVERSET S 62 B	☐
	<u>204 62 62 W</u>	COVERSET S 62 W	☐
	<u>204 80 80 ANO</u>	COVERSET S 80 ANO	☐
	<u>204 80 80 B</u>	COVERSET S 80 B	☐
	<u>204 80 80 W</u>	COVERSET S 80 W	☐
	<u>204 90 90 ANO</u>	COVERSET S 90 ANO	☐
	<u>204 90 90 B</u>	COVERSET S 90 B	☐
	<u>204 90 90 W</u>	COVERSET S 90 W	☐

les accessoires de suspension

	<u>328 10 01</u>	SUSPENSION TRIMLESS O.F.A.	☐
	Cutout dimension (mm): 62 (CONCRETE: 102)		
	<u>15225 0340 B</u>	SUSPENSION ST B	☐
	Cutout dimension (mm): 27		


INFORM SQ P475-9 DOWN 92767

25572 9220 W-W

15225 0340 W SUSPENSION ST W

☐

les accessoires pour connexions électriques



328 10 03 CONNECTION TRIMLESS O.F.A.

☐

Cutout dimension (mm): 62 (CONCRETE: 102)



15225 0360 B CONNECTION ST B

☐

Cutout dimension (mm): 43

15225 0360 W CONNECTION ST W

☐

Notes: