
DELTALIGHT




# SL19 - SPY 39 L 93020 MDL

**REFERENCE** 27032 9320 W

AVAILABLE IN
**BLACK** 27032 9320 B
**FLEMISH BRONZE** 27032 9320 FBR
**FLEMISH GOLD** 27032 9320 FG
**GOLD COLOURED** 27032 9320 GC
**WHITE** 27032 9320 W




View on website

| General info | |
|---|---|
| **LOCATION** | indoor |
| **INSTALLATION** | Low voltage systems Low voltage system mounted |
| **INGRESS PROTECTION** | IP20 |
| **WEIGHT (KG)** | 0.4 |
| **ADJUSTABILITY** | 0° to 85° swiveling, 355° rotatable |
| **INFORMATION** | REFLECTOR FL-20°<br>EXCL.LED POWER SUPPLY 48V-DC |

| Electrical info | |
|---|---|
| **ELECTRICAL** | 48V-DC |
| **CLASS** | III |
| **DIM TYPE** | MDL = 1-10V or DALI or push button |
| **ENERGY CLASS** | D |
| **CERTIFICATES** | CB, ENEC |

| Lightsource info | |
|---|---|
| **LIGHTSOURCE NAME** | LED |
| **LIGHTSOURCE** | LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm |
| **TM-30 VALUES** | Rf: 90 / Rg: 99 |
| **SDCM** | SDCM1 |
| **RISKGROUP** | RG1 |
| **LM80** | L90B10 > 50000 |
| **BEAMANGLE** | 20° |
| **LED TECHNICS (LIGHT SOURCE)** | 1089lm // 8,6W // 127lm/W |
| **LED TECHNICS (LUMINAIRE)** | 683lm // 9,9W // 69lm/W |

**Requirements**

SPY 39 L TUBE
LED POWER SUPPLY 48V-DC

**Options**

DIMMABLE MODULATOR

For detailed installation instructions, please consult the manual : **27032_XXX0_HAND.pdf**

DELTALIGHT

# SL19 - SPY 39 L 93020 MDL

27032 9320 W


## FINISH YOUR SPECIFICATION

### SMART 48

**# of Fixtures**


**Min current | Max current**

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.




**300 90 011** SMART 48 MODULATOR DIM9 — 19

**Dimtype: 1-10V or DALI or push button**




**300 90 012** SMART 48 MODULATOR WD — 19


**Dimtype: WDL = wireless dimmable**

### LED power supplies

**# of Fixtures**


**Min current | Max current**

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.





**300 89 48 100** LED POWER SUPPLY 48V-DC / 100W DIN — 10

**Dimtype: non-dimmable**




**300 89 48 240** LED POWER SUPPLY 48V-DC / 240W DIN — 24


**Dimtype: non-dimmable**




**21012 0230** LED POWER SUPPLY 48V-DC / 100W — 10

**Dimtype: non-dimmable**

**Cutout dimension (mm): 40**




**21012 0240** LED POWER SUPPLY 48V-DC / 200W — 20

**Dimtype: non-dimmable**


**Cutout dimension (mm): 40**

DELTALIGHT



# SL19 - SPY 39 L 93020 MDL

27032 9320 W

## Finish your product

| | | | |
|---|---|---|---|
|   | **24144 0020 B** | SPY 39 L TUBE B | ☐ |
| | **24144 0020 FBR** | SPY 39 L TUBE FBR | ☐ |
| | **24144 0020 FG** | SPY 39 L TUBE FG | ☐ |
| | **24144 0020 GC** | SPY 39 L TUBE GC | ☐ |
| | **24144 0020 W** | SPY 39 L TUBE W | ☐ |

## COMPATIBLE COMPOSABLES

| SHIFTLINE 19 profile | | Available Colours |
|---|---|---|
|   | **27011 0050** SL19 - PROFILE 2m | ● ○ |
|   | **27011 0060** SL19 - PROFILE 3m | ● ○ |

Notes: