



ENTERO SQ-M TRIMLESS IP TW 96518



28555 9010 B

AVAILABLE IN

BLACK 28555 9010 B

FULL WHITE 28555 9010 FW

GOLD COLOURED 28555 9010 GC



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	rectangle - Ø KIT
RECESSED DEPTH (MM)	150
INGRESS PROTECTION	IP44/20
WEIGHT (KG)	0.405
ADJUSTABILITY	0° to 20° swiveling, 355° rotatable
INFORMATION	REFLECTOR SP-18° EXCL.LED POWER SUPPLY 500mA-DC TW - (DALI DT8)

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 9W / CRI>90 (R9: 50) / 2700K-6500K / 1087lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	18°
LED TECHNICS (LIGHT SOURCE)	1087lm // 9W // 121lm/W
LED TECHNICS (LUMINAIRE)	708lm // 10,4W // 68lm/W

Requirements

MOUNTING KIT ENTERO SQUARE M

LED POWER SUPPLY 500mA-DC TW (Remote)

For detailed installation instructions, please consult the manual : [28555_XXX0_HAND.pdf](#)

DELTALIGHT

ENTERO SQ-M TRIMLESS IP TW 96518

28555 9010 B

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	 28400 0050 - MOUNTING KIT ENTERO SQ-M Required
 Plasterboard	 28400 0050 - MOUNTING KIT ENTERO SQ-M Required
 Stucanet	 28400 0050 - MOUNTING KIT ENTERO SQ-M Required
 Wood	 28400 0050 - MOUNTING KIT ENTERO SQ-M Required
 Concrete + plaster	 28400 0050 - MOUNTING KIT ENTERO SQ-M Required
 Lintel + plaster	 28400 0050 - MOUNTING KIT ENTERO SQ-M Required
 Hollow-core slab + plaster	 28400 0050 - MOUNTING KIT ENTERO SQ-M Required
 Stretched ceiling	 28400 0110 - MOUNTING KIT ENTERO SQ-M CSC Required
	 28400 0170 - MOUNTING KIT ENTERO SQ-M WSC Required

FINISH YOUR SPECIFICATION


LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




21012 0355 LED POWER SUPPLY 500mA-DC 2CH TW DIM5

2

Dimtype: DALI

Cutout dimension (mm): 85

Mounting kits



28400 0050 MOUNTING KIT ENTERO SQ-M


Cutout dimension (mm): 122 x 122

DELTALIGHT

ENTERO SQ-M TRIMLESS IP TW 96518

28555 9010 B

Mounting kits stretched ceiling



28400 0110 MOUNTING KIT ENTERO SQ-M CSC



28400 0170 MOUNTING KIT ENTERO SQ-M WSC



Notes: