
DELTALIGHT



SUPERLOOP POWERBOX L 700mA DIM1

REFERENCE 321 55 207 ED1 B

AVAILABLE IN
BLACK 321 55 207 ED1 B
WHITE 321 55 207 ED1 W



View on website

General info	
LOCATION	indoor
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.697
INFORMATION	Suited for 2 or 3 cable supension INCL.DIMMABLE LED POWER SUPPLY 700mA / 36W λ > 0,9 Inrush current : 5A - 50µs @ 230V-AC Max. 50 units on circuit breaker B 16A

Electrical info	
CLASS	II
POWER SUPPLY	YES
DIM TYPE	1-10V

For detailed installation instructions, please consult the manual : **321_55_207_ED1_HAND.pdf**

WHERE USED

321 107 92	SUPERLOOP HC 70 SBL 927
321 107 93	SUPERLOOP HC 70 SBL 930
321 109 92	SUPERLOOP HC 90 SBL 927
321 109 93	SUPERLOOP HC 90 SBL 930
321 207 93	SUPERLOOP HC 70 SPR 930
321 209 93	SUPERLOOP HC 90 SPR 930
321 507 92	SUPERLOOP VC 70 SBL 927
321 507 93	SUPERLOOP VC 70 SBL 930
321 509 92	SUPERLOOP VC 90 SBL 927
321 509 93	SUPERLOOP VC 90 SBL 930
20561 9200	SUPERLOOP PLUS HC 70 SBL 927
20561 9300	SUPERLOOP PLUS HC 70 SBL 930
20562 9200	SUPERLOOP PLUS HC 90 SBL 927
20562 9300	SUPERLOOP PLUS HC 90 SBL 930
20570 9200	SUPERLOOP HC SBL OVAL S 927
20570 9300	SUPERLOOP HC SBL OVAL S 930
20572 9200	SUPERLOOP SLIM IN 70 SBL 927
20572 9300	SUPERLOOP SLIM IN 70 SBL 930
20573 9200	SUPERLOOP SLIM IN 90 SBL 927
20573 9300	SUPERLOOP SLIM IN 90 SBL 930
20576 9200	SUPERLOOP SLIM OUT 70 SBL 927

DELTALIGHT

SUPERLOOP POWERBOX L 700mA DIM1

321 55 207 ED1 B

20576 9300	SUPERLOOP SLIM OUT 70 SBL 930
20577 9200	SUPERLOOP SLIM OUT 90 SBL 927
20577 9300	SUPERLOOP SLIM OUT 90 SBL 930
20580 9200	SUPERLOOP SLIM DOWN 70 SBL 927
20580 9300	SUPERLOOP SLIM DOWN 70 SBL 930

Notes: