





LOGIC LINEAR 440 HONEYCOMB  
94040

30812 9430 N

AVAILABLE IN  
ANTHRACITE 30812 9430 N



 [View on website](#)



| General info                         |                                                                                                                                                                 |
|--------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| LOCATION                             | outdoor                                                                                                                                                         |
| INSTALLATION                         | Floor Recessed                                                                                                                                                  |
| CUTOUT SHAPE/SIZE (MM)               | rectangle - BOX                                                                                                                                                 |
| RECESSED DEPTH (MM)                  | 140                                                                                                                                                             |
| INGRESS PROTECTION                   | IP67                                                                                                                                                            |
| PROTECTION AGAINST MECHANICAL IMPACT | IK09                                                                                                                                                            |
| WEIGHT (KG)                          | 2                                                                                                                                                               |
| ADJUSTABILITY                        | non adjustable                                                                                                                                                  |
| INFORMATION                          | 8 x LENS WFL-40°<br>INCL.HONEYCOMB<br>INCL.LED POWER SUPPLY 650mA-DC<br>INCL.1 x CABLE H05 RN-F 3 x 0.75mm² 0,5m<br>INCL.IP68 CONNECTOR 3P<br>ESG 8mm max.500kg |
| Electrical info                      |                                                                                                                                                                 |
| ELECTRICAL                           | 220-240V / 0 50-60Hz                                                                                                                                            |
| CLASS                                | I                                                                                                                                                               |
| POWER SUPPLY                         | YES                                                                                                                                                             |
| DIM TYPE                             | non-dimmable                                                                                                                                                    |
| ENERGY CLASS                         | E                                                                                                                                                               |
| CERTIFICATES                         | CB, ENEC, EPD, RCM                                                                                                                                              |
| Lightsource info                     |                                                                                                                                                                 |
| LIGHTSOURCE NAME                     | LED                                                                                                                                                             |
| LIGHTSOURCE                          | LED cluster 14,4W / CRI>90 (R9: 64) / 4000K / 1949lm                                                                                                            |
| TM-30 VALUES                         | Rf: 91 / Rg: 100                                                                                                                                                |
| SDCM                                 | SDCM3                                                                                                                                                           |
| RISKGROUP                            | RG2                                                                                                                                                             |
| LM80                                 | L80 > 150000                                                                                                                                                    |
| BEAMANGLE                            | 40°                                                                                                                                                             |
| LED TECHNICS (LIGHT SOURCE)          | 1949lm // 14,4W // 131lm/W                                                                                                                                      |
| LED TECHNICS (LUMINAIRE)             | 761lm // 16,6W // 46lm/W                                                                                                                                        |
| Requirements                         |                                                                                                                                                                 |
| LOGIC LINEAR BOX                     |                                                                                                                                                                 |

For detailed installation instructions, please consult the manual : [30812\\_XXX0\\_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Ground mounting boxes



**30810 0010** LOGIC LINEAR 440 BOX


☐

Cutout dimension (mm): 480 x 150

Waterproof connection parts



**431 99 02** IP68 JUNCTION BOX 4P

☐

**21034 0150** IP68 Y-CONNECTOR 5P

☐

Notes: