



OML50 - PRISMATIC LENS DU HO 1968mm 930 DIM5

31636 9305 B

AVAILABLE IN
BLACK 31636 9305 B

 [View on website](#)



General info

LOCATION	indoor
INGRESS PROTECTION	IP20
WEIGHT (KG)	2.8
INFORMATION	INCL.DIMMABLE LED POWER SUPPLY (DALI-2 standard) CABLING 1 CIRCUIT

Electrical info

ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	D
CERTIFICATES	EPD, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN: LED cluster 46,5W / CRI>90 (R9: 50) / 3000K / 7140lm UP: LED cluster 36,3W / CRI>90 (R9: 50) / 3000K / 5242lm
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	DOWN: 7140lm // 46,5W // 153lm/W UP: 5242lm // 36,3W // 145lm/W

Options

WIRELESS CONTROL DIM5

Notes: