



## LOGIC LINEAR 440 HONEYCOMB 92725 DIM5

30812 9225 N

AVAILABLE IN  
**ANTHRACITE** 30812 9225 N



[View on website](#)



### General info

|                                             |                                                                                                                                                                                  |
|---------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>LOCATION</b>                             | outdoor                                                                                                                                                                          |
| <b>INSTALLATION</b>                         | Floor Recessed                                                                                                                                                                   |
| <b>CUTOUT SHAPE/SIZE (MM)</b>               | rectangle - BOX                                                                                                                                                                  |
| <b>RECESSED DEPTH (MM)</b>                  | 140                                                                                                                                                                              |
| <b>INGRESS PROTECTION</b>                   | IP67                                                                                                                                                                             |
| <b>PROTECTION AGAINST MECHANICAL IMPACT</b> | IK09                                                                                                                                                                             |
| <b>WEIGHT (KG)</b>                          | 2                                                                                                                                                                                |
| <b>ADJUSTABILITY</b>                        | non adjustable                                                                                                                                                                   |
| <b>INFORMATION</b>                          | 8 x LENS FL-25°<br>INCL.HONEYCOMB<br>INCL.DIMMABLE LED POWER SUPPLY 650mA-DC<br>INCL.1 x CABLE H07 RN-F 5 x 1mm <sup>2</sup> 0,5m<br>INCL.IP68 CONNECTOR 5P<br>ESG 8mm max.500kg |

### Electrical info

|                     |                      |
|---------------------|----------------------|
| <b>ELECTRICAL</b>   | 220-240V / 0 50-60Hz |
| <b>CLASS</b>        | I                    |
| <b>POWER SUPPLY</b> | YES                  |
| <b>DIM TYPE</b>     | DALI                 |
| <b>ENERGY CLASS</b> | F                    |
| <b>CERTIFICATES</b> | CB, ENEC, EPD, RCM   |

### Lightsource info

|                                    |                                                      |
|------------------------------------|------------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                                  |
| <b>LIGHTSOURCE</b>                 | LED cluster 14,4W / CRI>90 (R9: 50) / 2700K / 1644lm |
| <b>TM-30 VALUES</b>                | Rf: 91 / Rg: 100                                     |
| <b>SDCM</b>                        | SDCM3                                                |
| <b>RISKGROUP</b>                   | RG2                                                  |
| <b>LM80</b>                        | L80 > 150000                                         |
| <b>BEAMANGLE</b>                   | 25°                                                  |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 1644lm // 14,4W // 111lm/W                           |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 666lm // 16,6W // 40lm/W                             |

### Requirements

LOGIC LINEAR BOX

For detailed installation instructions, please consult the manual : [30812\\_XXX5\\_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Ground mounting boxes




**30810 0010** LOGIC LINEAR 440 BOX

☐

Cutout dimension (mm): 480 x 150

Waterproof connection parts



**21034 0150** IP68 Y-CONNECTOR 5P

☐

Notes: