



INFORM ST 1104 92767

REFERENCE

25502 9220 W-W

AVAILABLE IN

BLACK-BLACK 25502 9220 B-B
BLACK-FLEMISH GOLD 25502 9220 B-FG
WHITE-BLACK 25502 9220 W-B
WHITE-WHITE 25502 9220 W-W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	rectangle - 38 x 1117
RECESSED DEPTH (MM)	40
THICKNESS OF MOUNTING SURFACE (MM)	max.12,5
INGRESS PROTECTION	IP20
WEIGHT (KG)	1
ADJUSTABILITY	non adjustable
INFORMATION	48 x REFLECTOR FL-67° EXCL. LED POWER SUPPLY 400/600mA-DC

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 14,1-22,3W / CRI>90 (R9: 50) / 2700K / 2026-2928lm
TM-30 VALUES	Rf: 93 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
BEAMANGLE	67°
LED TECHNICS (LIGHT SOURCE)	2928lm // 22,3W // 131lm/W
LED TECHNICS (LUMINAIRE)	2556lm // 25,6W // 100lm/W

Requirements



INFORM POWER SUPPLY 25W

For detailed installation instructions, please consult the manual : [25502_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
	System ceiling -
	Plasterboard -
	Wood -

FINISH YOUR SPECIFICATION

LED power supplies		# of Fixtures
 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
	25510 0395 INFORM POWER SUPPLY 25W DIM5	1
Dimtype: DALI		
	25510 0440 INFORM POWER SUPPLY 25W	1
Dimtype: non-dimmable		

Notes: