




OML50 - INFORM D HE 3280mm 8+16+8LED 93063 DIM5

31424 9335 B

BESCHIKBAAR IN
ZWART 31424 9335 B



[Bekijk op website](#)



Algemene info

LOCATIE	binnen
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	0
INFO	CLUSTER DOWN: 1545lm/m INCL.DIMMABLE LED POWER SUPPLY (DALI-2 standard) CABLING 1 CIRCUIT

Elektrische info

ELEKTRISCH	220-240V / 0 50-60Hz
KLASSE	I
VOEDING INBEGREPEN	YES
DIM TYPE	DALI
ENERGIE KLASSE	D
CERTIFICATES	EPD, RCM

Info lichtbron

LIGHTSOURCE NAME	LED
LICHTBRON	LED cluster 32,6W / CRI>90 (R9: 50) / 3000K / 5069lm
TM-30 WAARDEN	Rf: 92 / Rg: 100
SMD	SDCM3
RISK-GROEP	RG1
LM80	L80 > 60000
BEAMANGLE	63°
LED TECHNIEK (LICHTBRON)	5069lm // 32,6W // 155lm/W

Opties

WIRELESS CONTROL DIM5

Notes: