

VIZIR / HEDRA



Listing

ETL certified to US and Canadian safety standards.

Warranty

5-year limited warranty.

Hedra & Vizir add refinement, finesse and color to the range. They are characterized by an atypical hinge, a design element that not only catches the eye, but also serves as storage for technical parts inside the luminaire. Next to black and white, the Hedra is available in the Gold Colored anodization and Black Bronze finishes, with faceted texture. The faceted design of the Hedra captures and reflects the ambient light with an ever-changing look as result. Vizir is a smooth cylinder, offered in the same beautiful finishes.

Specification	Clip	On
LED Aperture	1 ²⁷ / ₃₂ "	
Ceiling Cutout:	2"	Surface Mounted
Installation Method:	Semi-Recessed	4" J-Box
Adjustability:	Adjustable 0-90° / 355°	
Rating:	IP20	

Performance	8°	33°
LED Maintenance:	L90>76,200h	L70>50,000h
McAdam Step:	2	
CRI:	90	
*LP:	3.9W	7.1W
*MP:	5.7W	10.4W
*HP:	15W	

Delivered Lumens	2700K		3000K		3500K	
Optic:	8°	33°	8°	33°	8°	33°
Vizir/Hedra S LP:	294Lm	392Lm	294Lm	392Lm	294Lm	392Lm
Vizir/Hedra S MP:	397Lm	544Lm	397Lm	544Lm	397Lm	544Lm
Vizir/Hedra L LP:		395Lm		411Lm		424Lm
Vizir/Hedra L MP:		526Lm		549Lm		566Lm
Vizir/Hedra L HP:		731Lm		762Lm		786Lm

Ordering

ALL BOXES MUST BE FILLED IN TO CORRECTLY ORDER

Example: HDR-MP3330A-GC-B-B-CLRS-IAT_RMTD8-120

Luminaire	Length	Power*	Optic	CCT	Function	Finish	Inner Finish	Style	Installation	Application	Controls***
HDR HEDRA (faceted)	S Standard	LP Low Power	08 8°	27 2700K	A Adjustable	B-B⁽²⁾ Black-Black	B Black	CL Clip Semi-Recessed	FL Flush kit for mud into drywall	IAT⁽⁹⁾ New Construction-IC AIRTIGHT Housing	D1-UNV 0-10V dim 120-277V
VZR VIZIR (smooth)		MP Medium Power		30 3000K		BBR-B Black Bronze-Black	FBR Flemish Bronze		RS Surface trim for rigid surface	IAT_RMT New Construction-IC AIRTIGHT Housing + Remote Power Supply	D8-120 FE ELV dim 120V
	S Standard	LP Low Power	33 33°	35 3500K		GC-B Gold Colored-Black	FG Flemish Gold			RMT Remote Power Supply	
	L Long	MP Medium Power				W-W White-White	W White	ON Surface Canopy	MK Mud kit into drywall over 4" junction box PRB Black coverplate for 4" junction box PRW White coverplate for 4" junction box	RMT Remote Power Supply	

¹ Only available with Length L

² Only available with Luminaire HDR

³ Only available with Power MP

*** Contact factory for additional dimming options.


Related Products

Vizir/Hedra 2S (double surface), Hedra C (pendant), Superloop-Vizir/Hedra MDL




Finish Options


HEDRA CLIP S




HEDRA CLIP L





HEDRA ON S



HEDRA ON L



INNER FINISH



Finish Options (Cont'd)

VIZIR CLIP S



VIZIR CLIP L



VIZIR ON S




VIZIR ON L




FL - FLUSH MOUNTING KIT

MK - MUD KIT 1

PRB/PRW COVERPLATE R 113



Requires 4" junction box




BLACK or WHITE
Requires 4" junction box

Accessories




HONEYCOMB
473 03 01 B



SOFTENING LENS
473 03 04

Photometric Data


VIZIR/HEDRA



Installation Options

IC AIRTIGHT


S-SMALL:
A:12"-5/8 x B:11"-1/16 x C:4"-13/16
A:323mm x B:281mm x C:122mm



- Low Profile under 5" Height
- New Construction Airtight
- For use in insulated ceiling
- Chicago Plenum
- ETL Listed
- Hangerbar expand to 24"-23/32 or 15"-3/32 - reduce to 12"-23/32 or 9"- 1/32
- Damp rated
- Patented System for easy driver servicing from room side

Remote Driver (With Controls D8)


A: 8" x B: 2"-1/2 x C: 2"-1/2
A: 203mm x B: 64mm x C: 64mm



- For Remote application
- ETL Listed
- Damp rated

Remote Driver (With Controls D1)

A: 8" x B: 2"-3/16 x C: 4"-1/4
A: 203mm x B: 72mm x C: 108mm



- For Remote application
- ETL Listed
- Damp rated



Driver Options

D1 (With Application IAT_RMT or RMT)

- Dimming Control 0-10V
- Dimming Range 1-100%
- Dim to off yes at 0.7mA
- Power Factor @ Full Load >0.9
- Efficiency @ Full Load ≥87
- THD @ Full Load <20%
- Title 24 Compliant

Dimmer Compatibility

- Leviton IP710-DLZ
- Lutron DDTV-XX
- WattStopper ADF-120277
- Synergy Lighting Controls ISD BC

D1

- Dimming Control 0-10V
- Dimming Range 1-100%
- Dim to off yes at 0.8V, 1V, 1.2V, or N/A
- Power Factor @ Full Load >0.9 under 120Vac Input with 80~100% load condition (for all output currents)
- Efficiency @ Full Load ≥86
- THD @ Full Load <20% under 120Vac input with 80~100% load condition (for all output currents)

Dimmer Compatibility

- Leviton IP710-LFZ / IP710-DLX
- Lutron DDTV/DVSTV/DVSCTV/DVSCS

D8 (With Power HP)

- Dimming Control Phase Control
- Dimming Range 20-100%
- Dim to off yes
- Power Factor @ Full Load >0.9
- Efficiency @ Full Load ≥80
- THD @ Full Load <10%

Dimmer Compatibility

- Leviton IPE04-1LZ
- Lutron DVELV-300P

D8

- Dimming Control Phase Control
- Dimming Range 10-100%
- Dim to off no
- Power Factor @ Full Load >0.9
- Efficiency @ Full Load ≥78
- THD @ Full Load <12%

Dimmer Compatibility

- Leviton IPE04-1LZ
- Lutron DVELV-300P

As technology changes, please use information above as guidance. For most recent updated information please contact factory. Specifications subject to change without notice.