





## M20/M26H - SPY 66 93045 MDL

23327 9330 W

AVAILABLE IN  
**BLACK** 23327 9330 B  
**WHITE** 23327 9330 W



 [View on website](#)



### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Low voltage systems Low voltage system mounted
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	0.6
<b>ADJUSTABILITY</b>	0° to 90° swiveling, 355° rotatable
<b>INFORMATION</b>	REFLECTOR WFL-45° EXCL.LED POWER SUPPLY 48V-DC Optional REFLECTORS 18° & 30° available

### Electrical info

<b>ELECTRICAL</b>	48V-DC
<b>CLASS</b>	III
<b>DIM TYPE</b>	MDL = 1-10V or DALI or push button
<b>ENERGY CLASS</b>	E
<b>CERTIFICATES</b>	CB, ENEC, EPD

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED array 25W / CRI>90 (R9: 52) / 3000K / 2811lm
<b>TM-30 VALUES</b>	rf: 90 / Rg: 99
<b>SDCM</b>	SDCM1
<b>RISKGROUP</b>	RG1
<b>LM80</b>	L90B10 > 50000
<b>BEAMANGLE</b>	45°
<b>LED TECHNICS (LIGHT SOURCE)</b>	2811lm // 25W // 112lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	1929lm // 28,8W // 67lm/W

### Remarks

Take a look at our [MAGNETIC PROFILES](#) movie

### Requirements

SPY 66 TUBE  
 LED POWER SUPPLY 48V-DC

### Options

DIMMABLE MODULATOR

### Accessories

HONEYCOMB 57

# DELTALIGHT

## M20/M26H - SPY 66 93045 MDL


23327 9330 W

For detailed installation instructions, please consult the manual : [23327\\_XXX0\\_HAND.pdf](#)

### FINISH YOUR SPECIFICATION

#### Current supply

#### # of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




**21032 0030** SMART 48 MODULATOR PLUG-IN WD

Dimtype: WDL = wireless dimmable

6

#### SMART 48

#### # of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



**300 90 011** SMART 48 MODULATOR DIM9

Dimtype: 1-10V or DALI or push button

6




**300 90 012** SMART 48 MODULATOR WD

Dimtype: WDL = wireless dimmable

6

#### LED power supplies

#### # of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



**300 89 48 100** LED POWER SUPPLY 48V-DC / 100W DIN

Dimtype: non-dimmable

3

# DELTALIGHT

## M20/M26H - SPY 66 93045 MDL


23327 9330 W



**300 89 48 240** LED POWER SUPPLY 48V-DC / 240W DIN

8

Dimtype: non-dimmable




**21012 0230** LED POWER SUPPLY 48V-DC / 100W

3

Dimtype: non-dimmable

Cutout dimension (mm): 40




**21012 0240** LED POWER SUPPLY 48V-DC / 200W

7

Dimtype: non-dimmable


Cutout dimension (mm): 40

### Light altering devices



**24611 0150 B** HONEYCOMB 57 SINGLE USE B

### Finish your product



**24611 0100 B** SPY 66 TUBE B

**24611 0100 FBR** SPY 66 TUBE FBR

**24611 0100 FG** SPY 66 TUBE FG

**24611 0100 GC** SPY 66 TUBE GC

**24611 0100 W** SPY 66 TUBE W

# DELTALIGHT

## M20/M26H - SPY 66 93045 MDL

23327 9330 W

### Replaceable reflector / lens



**24611 0220** SPY 66 REFLECTOR 18°



**24611 0230** SPY 66 REFLECTOR 30°




**24611 0240** SPY 66 REFLECTOR 45°




## COMPATIBLE COMPOSABLES

### SHIFTLINE M26H profile


### Available Colours




**23359 0000** SLM26H - PROFILE



**23359 0010** SLM26H - PROFILE 1m



**23359 0020** SLM26H - PROFILE 2m



**23359 0030** SLM26H - PROFILE 3m



### SPLITLINE M20 ST profile

### Available Colours



**23397 0000** SPM20 ST - PROFILE



# DELTALIGHT

## M20/M26H - SPY 66 93045 MDL

23327 9330 W



**23397 0020** SPM20 ST - PROFILE 2m




**23397 0030** SPM20 ST - PROFILE 3m




### SPLITLINE M20 profile


### Available Colours




**420 20 10 00** SPM20 - PROFILE 1m



**420 20 20 00** SPM20 - PROFILE 2m



**420 20 30 00** SPM20 - PROFILE 3m



**23301 0000** SPM20 - PROFILE B



Notes: