





ELBO BRIDGE P 20 930

223 122 93 B

AVAILABLE IN
ALU GREY 223 122 93 A
BLACK 223 122 93 B



[View on website](#)



General info

LOCATION	outdoor
INSTALLATION	Floor Surface mounted
INGRESS PROTECTION	IP55
WEIGHT (KG)	1.3
ADJUSTABILITY	non adjustable
INFORMATION	INCL.GLASS OPAL INCL.LED POWER SUPPLY 350mA-DC

Electrical info

ELECTRICAL	100-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
ENERGY CLASS	F
CERTIFICATES	CB, EAC, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 4,1W / CRI>90 / 3000K / 380lm
SDCM	SDCM2
RISKGROUP	RG2 (threshold 0,6m)
LED TECHNICS (LIGHT SOURCE)	380lm // 4,1W // 95lm/W
LED TECHNICS (LUMINAIRE)	259lm // 4,7W // 55lm/W


Options

PIN 4
 CBOX
 IP68 CONNECTION KIT
 IP68 CONNECTOR 3P

For detailed installation instructions, please consult the manual : [223 122 83 HAND.pdf](#)

FINISH YOUR SPECIFICATION


Waterproof connection parts



216 12 00 CBOX

☐

Cutout dimension (mm): 142 x 142




216 12 01 IP68 CONNECTION KIT

☐

216 12 02 IP68 CONNECTOR 3P

☐

Pins and plates for bollards



229 01 04 PIN 4

☐

Notes: