



OML50 - PRISMATIC LENS DU HO 1312mm EM-3H 930 DIM5

31227 9305 B

BESCHIKBAAR IN
ZWART 31227 9305 B



[Bekijk op website](#)



Algemene info

LOCATIE	binnen
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	2.2
INFO	INCL.DIMMABLE LED POWER SUPPLY (DALI-2 standard) CABLING 1 CIRCUIT

Elektrische info

INGANGSSPANNING	220-240V / 0 50-60Hz
KLASSE	I
VOEDING	YES
DIM TYPE	DALI
ENERGIE KLASSE	D
CERTIFICATEN	EPD, RCM

Info lichtbron

LIGHTSOURCE NAME	LED
LICHTBRON	DOWN: LED cluster 31W / CRI>90 (R9: 50) / 3000K / 4760lm UP: LED cluster 24,2W / CRI>90 (R9: 50) / 3000K / 3494lm
TM-30-15 WAARDEN	Rf: 92 / Rg: 100
SDCM	SDCM3
RISK-GROEP	RG1
LM80	L80 > 60000
LED TECHNIEK (LICHTBRON)	DOWN: 4760lm // 31W // 153lm/W UP: 3494lm // 24,2W // 145lm/W

Opties

WIRELESS CONTROL DIM5

Notes: