



OML50 - PRISMATIC LENS DU HO 1312mm EM-3H 930 DIM5

31227 9305 B

BESCHIKBAAR IN
ZWART 31227 9305 B



[Bekijk op website](#)



| Algemene info | |
|---------------------------------|--|
| LOCATIE | binnen |
| STOF EN WATERDICHTHEID | IP20 |
| GEWICHT (KG) | 2.2 |
| INFO | INCL.DIMMABLE LED POWER SUPPLY (DALI-2 standard) CABLING 1 CIRCUIT |
| Elektrische info | |
| ELEKTRISCH | 220-240V / 0 50-60Hz |
| KLASSE | I |
| VOEDING INBEGREPEN | YES |
| DIM TYPE | DALI |
| ENERGIE KLASSE | D |
| CERTIFICATES | EPD, RCM |
| Info lichtbron | |
| LIGHTSOURCE NAME | LED |
| LICHTBRON | DOWN: LED cluster 31W / CRI>90 (R9: 50) / 3000K / 4760lm UP: LED cluster 24,2W / CRI>90 (R9: 50) / 3000K / 3494lm |
| TM-30 WAARDEN | Rf: 92 / Rg: 100 |
| SMDC | SDCM3 |
| RISK-GROEP | RG1 |
| LM80 | L80 > 60000 |
| LED TECHNIEK (LICHTBRON) | DOWN: 4760lm // 31W // 153lm/W UP: 3494lm // 24,2W // 145lm/W |

Opties

WIRELESS CONTROL DIM5

Notes: