
DELTALIGHT




M26L - LED LINE OK 930 DIM5

REFERENCE 29316 9305 B

AVAILABLE IN
BLACK 29316 9305 B
WHITE 29316 9305 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.4
ADJUSTABILITY	355° swiveling
INFORMATION	EXCL.LED POWER SUPPLY 48V-DC

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	E

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED flex 18W / CRI>90 (R9: 60) / 3000K / 2240lm
SDCM	SDCM3
LM80	L70 > 30000
LED TECHNICS (LIGHT SOURCE)	2240lm // 18W // 124lm/W
LED TECHNICS (LUMINAIRE)	934lm // 20,7W // 45lm/W

Remarks

Take a look at our MAGNETIC PROFILES movie

Requirements

LED POWER SUPPLY 48V-DC

For detailed installation instructions, please consult the manual : **29316_XXX5_HAND.pdf**

DELTALIGHT

M26L - LED LINE OK 930 DIM5

29316 9305 B


FINISH YOUR SPECIFICATION

Current supply

of Fixtures

Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



21032 0030 SMART 48 MODULATOR PLUG-IN WD — 9 ☐


Dimtype: WDL = wireless dimmable

SMART 48

of Fixtures


Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



300 90 011 SMART 48 MODULATOR DIM9 — 9 ☐

Dimtype: 1-10V or DALI or push button



300 90 012 SMART 48 MODULATOR WD — 9 ☐


Dimtype: WDL = wireless dimmable

LED power supplies

of Fixtures


Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN — 4 ☐

Dimtype: non-dimmable




300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN — 11 ☐

Dimtype: non-dimmable

DELTALIGHT

M26L - LED LINE OK 930 DIM5


29316 9305 B



21012 0230 LED POWER SUPPLY 48V-DC / 100W — 4

Dimtype: non-dimmable

Cutout dimension (mm): 40







21012 0240 LED POWER SUPPLY 48V-DC / 200W — 9

Dimtype: non-dimmable

Cutout dimension (mm): 40

COMPATIBLE COMPOSABLES

SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)	Available Colours
 **23358 0000** SLM26L - PROFILE	
 **23358 0010** SLM26L - PROFILE 1m	
 **23358 0020** SLM26L - PROFILE 2m	
 **23358 0030** SLM26L - PROFILE 3m	

Notes: