



M26L - SPY 391 SOFT 93040 MDL

23437 9030 FG

AVAILABLE IN

BLACK 23437 9030 B

BRUSHED ALU 23437 9030 BRA

BRUSHED ANTHRACITE 23437 9030 BRAT

BRUSHED COPPER 23437 9030 BRCU

BRUSHED GOLD 23437 9030 BRG

BRUSHED OLD BRONZE 23437 9030 BROB

FLEMISH BRONZE 23437 9030 FBR

FLEMISH GOLD 23437 9030 FG

GOLD COLOURED 23437 9030 GC

PIANO BLACK 23437 9030 PB

WHITE 23437 9030 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 85° swiveling, 360° rotatable
INFORMATION	REFLECTOR WFL-40° EXCL.LED POWER SUPPLY 48V-DC

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	F
CERTIFICATION	EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 6W / CRI>90 (R9: 50) / 3000K-1800K / 623lm
RVALUES	rf: 90 / Rg: 99
SDMC	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	40°
LED TECHNICS (LIGHT SOURCE)	623lm // 6W // 105lm/W
LED TECHNICS (LUMINAIRE)	505lm // 6,9W // 73lm/W

Requirements






SPY 39 TUBE
LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR

For detailed installation instructions, please consult the manual : [23437_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Current supply		# of Fixtures
 web2print_power_supply_info_box		Min current Max current
 <u>21032 0030</u> SMART 48 MODULATOR PLUG-IN WD	16	☐
Dimtype: WDL = wireless dimmable		
SMART 48		# of Fixtures
 web2print_power_supply_info_box		Min current Max current
 <u>300 90 011</u> SMART 48 MODULATOR DIM9	16	☐
Dimtype: 1-10V or DALI or push button		
 <u>300 90 012</u> SMART 48 MODULATOR WD	16	☐
Dimtype: WDL = wireless dimmable		
LED power supplies		# of Fixtures
 web2print_power_supply_info_box		Min current Max current
 <u>300 89 48 100</u> LED POWER SUPPLY 48V-DC / 100W DIN	8	☐
Dimtype: non-dimmable		
 <u>300 89 48 240</u> LED POWER SUPPLY 48V-DC / 240W DIN	20	☐
Dimtype: non-dimmable		


DELTALIGHT

M26L - SPY 391 SOFT 93040 MDL



23437 9030 FG

	21012 0230	LED POWER SUPPLY 48V-DC / 100W	8	☐
	Dimtype: non-dimmable			
	Cutout dimension (mm): 40			
	21012 0240	LED POWER SUPPLY 48V-DC / 200W	17	☐
	Dimtype: non-dimmable			
	Cutout dimension (mm): 40			

Finish your product

	24144 0010 B	SPY 39 TUBE B	☐
	24144 0010 FBR	SPY 39 TUBE FBR	☐
	24144 0010 FG	SPY 39 TUBE FG	☐
	24144 0010 GC	SPY 39 TUBE GC	☐
	24144 0010 W	SPY 39 TUBE W	☐
	24144 0070	SPY 39 TUBE SBL	☐


COMPATIBLE COMPOSABLES

SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)			Available Colours
	32	<u>23358 0000</u> SLM26L - PROFILE	 
	32	<u>23358 0010</u> SLM26L - PROFILE 1m	 


DELTALIGHT

M26L - SPY 391 SOFT 93040 MDL

23437 9030 FG



23358 0020 SLM26L - PROFILE 2m



23358 0030 SLM26L - PROFILE 3m



Notes: