
DELTALIGHT




MINIGRID ON 150 92718 DIM8

REFERENCE 100044 9218 W-B

AVAILABLE IN
BLACK-BLACK 100044 9218 B-B
BLACK-WHITE 100044 9218 B-W
WHITE-BLACK 100044 9218 W-B
WHITE-WHITE 100044 9218 W-W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.1
ADJUSTABILITY	0° to 20° swiveling, 350° rotatable
INFORMATION	REFLECTOR SP-18° INCL.DIMMABLE LED POWER SUPPLY 500mA-DC

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	E

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 60) / 2700K / 1041lm
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	18°
LED TECHNICS (LIGHT SOURCE)	1041lm // 8,6W // 121lm/W
LED TECHNICS (LUMINAIRE)	863lm // 9,9W // 87lm/W

For detailed installation instructions, please consult the manual : **100044_XXX8_HAND.pdf**


DELTALIGHT

MINIGRID ON 150 92718 DIM8

100044 9218 W-B

FINISH YOUR SPECIFICATION

Miscellaneous control equipment



300 90 004 ED8 WIRELESS CONTROL DIM8

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 40

Notes: